

FA12S500

Switch mode power supply for industrial electronics

DESCRIPTION

The FA12S500 switching power supply provides a stable 12 V DC output voltage and a maximum current of 500 mA. It features two outputs with F-type connectors for reliable distribution. Compatible with a 100-240 V input range. Lightweight (0.5 kg), it facilitates integration into industrial installations.



ADVANTAGES

- Stable 12 V DC output voltage with a maximum current of 500 mA
- Two outputs with F-type connectors for reliable distribution
- Compatible with 100-240 V input range for various power sources
- Lightweight (0.5 kg) for easy integration in industrial environments



Updated: 10/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Input(s)	1
Output(s)	2
Connector Type (Vdc)	F
Frequency Band (MHZ)	47-862
Weight (Kg/U)	0.50

ELECTRICAL CHARACTERISTICS

Maximum Current. of Output (Ma)	500
Power Indicator	Led
Insertion Loss (dB)	<4
Range of Alimentation (Vdc)	100/240
Output Voltage (V)	12

TRANSMISSION CHARACTERISTICS

Frequency Band (MHZ)	47-862
----------------------	--------

ADDITIONAL INFORMATION

Frequency Band (MHZ)	47-862
----------------------	--------