FAQCF242

24Vdc switching power supply with 2 outputs

DESCRIPTION

24 Vdc power supply, 2 outputs in F and QuiCoax solution, designed to fit easily into junction boxes and ensure a reliable and secure connection.



ADVANTAGES

- Linear power supply
- Ultra-compact dimensions
- Compatible with 80x80mm flush-mount cabinet
- Easy to install in seconds
- Quicoax and F connection system
- QuiCoax Zamak cabinet for high protection
- LED operation indicator

Updated: 3/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE	
Dimensions (L x W x H)	62 x 60 x 22
Output(s)	2
Power supply	100/240
Frequency Band (MHZ)	47-1000
Weight (Kg/U)	0.16
ELECTRICAL CHARACTERISTICS	
Power supply	100/240
Maximum Currentimum (Ma)	150
Through Loss (dB)	<4
Output Voltage (V)	24
TRANSMISSION CHARACTERISTICS	
Frequency Band (MHZ)	47-1000
MECHANICAL CHARACTERISTICS	
Type of Connectors	QC (QuiCoax) / F
ADDITIONAL INFORMATION	
Product Packaging	Box of 1
Frequency Band (MHZ)	47-1000

Updated: 3/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.