

FHP215BLARCCA

FHP215BLARCCA - Speaker Cable - 2 x 1.50 mm² - Shielded and armored - Brown LSZH



DESCRIPTION

Shielded and armored 2 x 1.50 mm² speaker cable C1, designed for Public Address (PA) installations in demanding environments. The FHP215BLARCCA cable features braided shielding and steel tape armor, providing enhanced protection against mechanical damage and rodents. Its LSZH outer sheath reduces smoke and corrosive gas emissions in case of fire, ensuring better safety.



ADVANTAGES

- Complies with all fire safety standards for buildings housing people and equipment, as well as industrial buildings (e.g., nuclear power plants)
- High resistance to mechanical and environmental stresses



CONSTRUCTION & TECHNICAL PERFORMANCE

Construction (mm ²)	2 x 1,5 mm ²
Conductor material	Bare copper
Conductor cross-section	1,50 mm ²
Core composition	Multi-strand - Class 2
Insulation Material	LSZH Compound
Insulation Identification Method	Red, black
Assembly type	Multi conductors
Overall Shielding	Tinned copper braid
Inner Sheath Material	LSZH
Overall Armor	Armure Acier
Outer Sheath Material	LSZH
Nom. diameter of the outer sheath (mm)	11.00

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	600 V
---------------------	-------

MECHANICAL CHARACTERISTICS

Bending Radius in Fixed Installation	5 x Ø ext
--------------------------------------	-----------

ENVIRONMENTAL CHARACTERISTIC

Fire behaviour	IEC 60332-1, IEC 61034-1, IEC 61034-2, IEC 60754-1& 2
Fixed Use Temperature	- 15°C / + 70°C
Mobile Use Temperature	- 10°C / + 70°C

ADDITIONAL INFORMATION

Product Packaging	Drum of 1000m
-------------------	---------------