

HVDI4FOR48

**48 FO optical cable 12 modules of 4
FO G657A2 indoor grey**

DESCRIPTION

FTTH 4-fiber optical ring cable



ADVANTAGES

This optical cable is intended for building optical rings. It complies with the recommendations of the Objectif Fibre guide.

CASANOVA
/ ADALTRA

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Maximum attenuation coefficient at 1550nm (dB/Km)	0.3
Maximum attenuation coefficient from 1310nm to 1625nm (dB/Km)	0.4
Outer Sheath Material	LSZH
Color	Traffic White RAL 9016
Nom. diameter of the outer sheath (mm)	8
Number of Optical Fibers	Jusqu'à 48 FO
Number of Fibers per Tube	4
Weight (Kg/Km)	88

ELECTRICAL CHARACTERISTICS

Optical Performance	G657A2
---------------------	--------

TRANSMISSION CHARACTERISTICS

Data Transmission Standard	IEC 60793-2-50
----------------------------	----------------

MECHANICAL CHARACTERISTICS

Max Long-Term Tensile Strength	710
Max Short-Term Crush Resistance	300

ENVIRONMENTAL CHARACTERISTIC

CPR classification	Dca s2, d2, a2
Component Standard	TIA/EIA 455-21a

ADDITIONAL INFORMATION

Product Packaging	Drum of 2000m
-------------------	---------------

Additional Information

CABLE DE ROCADE FTTH - HVDI4FORXXX

N° Tube/fibre	Couleur	Jusqu'à 12 modules: Pas d'anneau	Jusqu'à 24 modules : 1 anneau
1	Rouge		
2	Bleu		
3	Vert		
4	Jaune		
5	Violet		
6	Blanc		
7	Orange		
8	Gris		
9	Marron		
10	Noir		
11	Turquoise		
12	Rose		

Noir
Sauf Tube N° 22
Anneau Blanc

Au-delà de 24 modules, le nombre d'anneaux noirs augmente

