

HVDI6FOR72

Indoor optical cable 72 fibers 12 modules of 6 fibers G657A2**DESCRIPTION**

FTTH 6-fiber optical ring cable



1. Fibre optique
2. Modules
3. Renfort FRP
4. Gaine LSZH Blanche RAL 9016
5. Ergot de découpe



Code couleur des fibres suivant TIA/EIA 455

ADVANTAGES

This optical cable is intended for building optical rings. It complies with the recommendations of the Objectif Fibre guide.

CASANOV@
/ADALTRA**CONSTRUCTION & TECHNICAL PERFORMANCE**

Maximum attenuation coefficient at 1550nm (dB/Km)	0.3
Maximum attenuation coefficient from 1310 nm to 1625 nm (dB/km)	0.4
Outer Sheath Material	LSZH
Color	Traffic White RAL 9016
Nom. diameter of the outer sheath (mm)	8
Number of Optical Fibers	72
Number of Fibers per Tube	6
Weight (Kg/Km)	0

ELECTRICAL CHARACTERISTICS

Optical Performance	G657A2
---------------------	--------

ENVIRONMENTAL CHARACTERISTIC

CPR classification acc.to EN50575	Dca s2, d2, a2
-----------------------------------	----------------

ADDITIONAL INFORMATION

Product Packaging	Drum of 2000m
-------------------	---------------

Updated: 13/10/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

ADDITIONAL INFORMATION

CABLE DE ROCADE FTTH - HVDI6FORXXX

N° Tube/fibre	Couleur	Jusqu'à 12 modules: Pas d'anneau	Jusqu'à 24 modules : 1 anneau
1	Rouge		
2	Bleu		
3	Vert		
4	Jaune		
5	Violet		
6	Blanc		
7	Orange		Noir Seul Tube N° 22 Anneau Blanc
8	Gris		
9	Marron		
10	Noir		
11	Turquoise		
12	Rose		

Au-delà de 24 modules, le nombre d'anneaux noirs augmente

