

MR525

2D BIS5 splitter

DESCRIPTION

BIS splitter with 5 inputs and 2 x 5 outputs, extended bandwidth from 5 to 2400 MHz. Low insertion loss: 3.8 dB at 862 MHz, 4.9 dB at 2400 MHz. Integrated DC pass-through, class A with +10 dB gain, ensuring efficient TV and satellite signal distribution in industrial environments.



ADVANTAGES

- BIS splitter with 5 inputs and 2 x 5 outputs, bandwidth 5 to 2400 MHz
- Low insertion loss: 3.8 dB at 862 MHz, 4.9 dB at 2400 MHz
- Integrated DC pass-through for equipment power supply
- Class A with +10 dB gain ensuring efficient signal distribution



Updated: 10/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Output(s)	2 x 5
Input	5
Frequency Band (MHZ)	5 - 2400
Weight (Kg/U)	2.00

ELECTRICAL CHARACTERISTICS

Class	A + 10dB
[nombre_entres_dc]	5
oui	CC
Through Loss (2400MHZ) (dB)	4,9
Through Loss (862MHZ) (dB)	3,8

TRANSMISSION CHARACTERISTICS

Frequency Band (MHZ)	5 - 2400
----------------------	----------

ADDITIONAL INFORMATION

Frequency Band (MHZ)	5 - 2400
----------------------	----------