MR929

2D BIS9 splitter

DESCRIPTION

BIS splitter with 9 inputs and 2 x 9 outputs, bandwidth from 5 to 2400 MHz. Low insertion loss: 3.8 dB at 862 MHz, 4.9 dB at 2400 MHz. Includes DC passage for simplified power supply. +10 dB gain in Class A ensuring stable and efficient performance.



ADVANTAGES

- BIS splitter with 5 inputs and 2 x 5 outputs, bandwidth 5 to 2400 MHz
- Low insertion loss: 3.8 dB at 862 MHz, 4.9 dB at 2400 MHz
- Integrated DC pass-through for equipment power supply
- Class A with +10 dB gain ensuring efficient signal distribution

Updated: 10/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE	
Output(s)	2 x 9
Input	9
Frequency Band (MHZ)	5 - 2400
Weight (Kg/U)	2.50
ELECTRICAL CHARACTERISTICS	
Class	A + 10dB
[nombre_entres_dc]	9
oui	CC
Through Loss (2400MHZ) (dB)	4,9
Through Loss (862MHZ) (dB)	3,8
TRANSMISSION CHARACTERISTICS	
Frequency Band (MHZ)	5 - 2400
ADDITIONAL INFORMATION	
Frequency Band (MHZ)	5 - 2400

Updated: 10/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.