SAC3PX

SAC3PX - combined input/output power connector base - Seetronic

DESCRIPTION

Base for power supply combining a male input (SAC3MPX) and a female output (SAC3FPX)



ADVANTAGES

- 2-pole + earth socket combining power input and output
- Connection on input only
- IP65 sealing rating and IP67 protection class for terminal equipment
- Max cable size: 2.50 mm²
- UL, TUV RH, CQC certified
- Rubber protective cover ref. CNAC-PX (not included)

Updated: 3/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE	
Color	Black
Body Material	Plastic
Connector Format	Embase
Connector Gender	Female / Male
Broadcast Connector Contact Material	Copper alloy
Connector Connection Type	To plug in
Weight (Kg/U)	0.25
ELECTRICAL CHARACTERISTICS	
Service Voltage (V)	250 V
TRANSMISSION CHARACTERISTICS	
Data Transmission Standard	IEC 61-9-84
MECHANICAL CHARACTERISTICS	
Insertion Cycle	1000
ADDITIONAL INFORMATION	
Product Packaging	Sans emballage

Updated: 3/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.