SE8FBH

SE8FBH - RJ45 Cat.6 socket for printed circuit board

DESCRIPTION

RJ45 socket - Cat.6 for horizontal mounting on printed circuit board. Rear mounting on a panel. Push-pull locking/unlocking.



ADVANTAGES

- Horizontal integration on printed circuit
- Secure locking and high reliability
- Class D - TIA/EIA 568B and ISO/IEC 11801 transmission standards
- High mechanical and chemical resistance
- Compact

Updated: 12/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE	
Color	Aluminium
Connector Format	Embase
Coding Type	Colour code 568 B
Weight (Kg/U)	0.025000
ELECTRICAL CHARACTERISTICS	
Operating voltage	75
TRANSMISSION CHARACTERISTICS	
Performance Category	Category 6
Data Transmission Standard	ISO / IEC 11801 Ed3 Class D
MECHANICAL CHARACTERISTICS	
Insertion Cycle	1000
ENVIRONMENTAL CHARACTERISTIC	
Operating Temperature	-30°C / +80°C
ADDITIONAL INFORMATION	
Product Packaging	Unit

Updated: 12/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.