SYT320SHCM10

SYT 3P AWG20 LSZH CPR Cca s1,d1, a1 grey telephone cable

DESCRIPTION

SYT1 SHC telephone cables are designed for high-speed digital indoor connections. Their halogen-free CPR Cca s1d1a1 sheath and IEC 60332-3 compliance make them ideal for industrial and nuclear sites.

ADVANTAGES

- CPR: Cca s1,d1,a1
- LSZH
- Color: Brown

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE	
Product Type	SYTxxyySHCMzz
Construction (mm²)	3 x 2 x AWG20
Conductor material	Bare copper
Conductor cross-section	AWG20
Core gauge	AWG20
Core composition	solid conductor
Insulation Material	PE
Assembly type	Pairs
Overall Shielding	Alu/pes tape with drain wire
Outer Sheath Material	LSZH
Color	Brown
Nom. diameter of the outer sheath (mm)	6.0
Weight (Kg/Km)	50
TRANSMISSION CHARACTERISTICS	
Characteristic Impedance (Ohms)	100 Ohms
MECHANICAL CHARACTERISTICS	
Bending Radius in Fixed Installation	10 x Ø ext
Bending Radius in Mobile Installation	20 x Ø ext
ENVIRONMENTAL CHARACTERISTIC	
CPR classification	Cca s1, d1, a1
Fire Behavior Type	Flame retardant IEC 60332-1 Fire retardant IEC 60332-3-24
UV Resistance	NO
Fixed Use Temperature	-30°C / +70°C
Mobile Use Temperature	-5°C / +70°C
Halogen-free Standard	IEC 60754-1/-2 IEC 61034-2
ADDITIONAL INFORMATION	
Product Packaging	Drum of 1000m

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.