

TRUNK24FOR144PC10

FTTH M4 trunk 50% connected

DESCRIPTION

50% pre-connected optical backbone cable - FTTH



Câble préconnecté conditionné sur touret en carton



Eclateur principal



Eclateur secondaire

ADVANTAGES

Pre-connected at 50%, allows for quick installation. Available in 24F, 48F, 72F, 96F, and 144F, all modulo 4.

CASANOV@
/ADALTRA

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Maximum attenuation coefficient at 1550nm (dB/Km)	0.3
Maximum attenuation coefficient from 1310nm to 1625nm (dB/Km)	0.4
Outer Sheath Material	900 µm
Nom. diameter of the outer sheath (mm)	30mm
Number of Optical Fibers	144
Weight (Kg/Km)	0.00

ELECTRICAL CHARACTERISTICS

Optical Performance	G657A2
---------------------	--------

ENVIRONMENTAL CHARACTERISTIC

Independent lab certification	No
-------------------------------	----

ADDITIONAL INFORMATION

Product Packaging	Drum
-------------------	------