ADALTRA

www.adaltra.com


ZZF3G15T1000

Harmonized LSZH H07ZZ-F 3G1.5mm² power cable - 500m drum, grey

DESCRIPTION

H07ZZ-F halogen-free elastomer cables, CPR Cca s1d1a1, are flexible and resistant to weather, UV, and mechanical stress. They connect equipment in demanding industrial environments and outdoors. LSZH — other constructions, sizes, and colors: please contact us.





ADVANTAGES

- LSZH
- CPR Cca s1,d1,a1
- Other structures, sections, color: please contact us.

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE	
Product Type	H07ZZ-F
Conductor material	Bare copper
Conductor cross-section	1,50 mm²
Core composition	IEC 60228 Cl. 5
Insulation Material	LSZH Compound
Insulation Identification Method	HD 308 S2
Assembly type	Multi conductors
Outer Sheath Material	LSZH
Color	Black
Weight (Kg/Km)	140
ELECTRICAL CHARACTERISTICS	
Service Voltage (V)	450 V / 750 V
Test voltage (V)	2.5 kV
Linear electrical resistance (Ω/Km)	Compliant with IEC 60228 class 5 standard
MECHANICAL CHARACTERISTICS	
Bending Radius in Fixed Installation	8 x Ø ext
Bending Radius in Mobile Installation	8 x Ø ext
Max Permissible Temperature on Core	90°C
Max Short-Circuit Temperature	250°C
IP rating	AD6 eau douce
ENVIRONMENTAL CHARACTERISTIC	
Independent lab certification	Yes
CPR classification	Cca s1, d1, a1
Fire behaviour	IEC 60332-1, IEC 60332-3-24
Fire Behavior Type	Flame retardant IEC 60332-1 Fire retardant IEC 60332-3-24
Fixed Use Temperature	-40°C / + 90°C
Mobile Use Temperature	-5°C / +70°C
Component Standard	EN 50525-3-21
Halogen-free Standard	IEC 60754-1/-2 IEC 61034-2
ADDITIONAL INFORMATION	
Product Packaging	Drum of 1000m

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.