


LCAEMPS122100SHB2x

**1-pair AWG22 Shielded LSZH B2ca s1a d1 a1
Cables - LonWorks****DESCRIPTION**

The LCAE MPS 122-100 SHB2 cable, PE insulated, low capacitance with CPR classification B2ca s1a,d1,a1, is used for LonWorks level IV applications. It is recommended for high-rise buildings (HRB), public access buildings (PAB), and infrastructures (tunnels, airports, nuclear sites).

**ADVANTAGES**

- Impedance 100 Ohms
- Overall shielding with aluminum tape
- Halogen-free sheath
- CPR: B2ca s1a,d1,a1

AXINDUS
/ ADALTRA**CONSTRUCTION & TECHNICAL PERFORMANCE**

Core gauge	AWG22
Conductor material	Tinned copper
Insulation Material	PE
Insulation Identification Method	White, Blue
Overall Shielding	Alu/pes tape with drain wire
Outer Sheath Material	LSZH
Color	White
Nom. diameter of the outer sheath (mm)	4.5
Construction (mm ²)	1 x 2 x AWG22

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	300 V
Test voltage (V)	1.2 kV
Linear electrical resistance (Ω /Km)	$\leq 59 \Omega/\text{km}$

TRANSMISSION CHARACTERISTICS

Propagation speed (%)	66
Characteristic Impedance (Ohms)	100 Ohms

Updated: 23/09/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

MECHANICAL CHARACTERISTICS

Bending Radius in Fixed Installation	8 x Ø ext
Bending Radius in Mobile Installation	15 x Ø ext

ENVIRONMENTAL CHARACTERISTIC

CPR classification	B2ca s1a, d1, a1
UV Resistance	NO
Fixed Use Temperature	-30°C / +70°C
Mobile Use Temperature	-5°C / +70°C
Installation Temperature	0°C
Fire behaviour	IEC 60332-1, Iec 60332 3 24 Cat. of
Fire Behavior Type	Flame retardant IEC 60332-1 Fire retardant IEC 60332-3-24
Halogen-free Standard	IEC 60754-1/-2 IEC 61034-2

ORDER INFORMATION

REFERENCE	CONSTRUCTION	Ø SHEATH NOM (MM)	WEIGHT (KG/KM)
LCAEMPS122100SHB2	1x2xAWG22	4.5	25