

MDC2152P510SHC

Composite cable (2x1.5 mm² + 2x(2x 5/10)) CPR Cca s1d1a1



DESCRIPTION

Composite cable (2x1.5 mm² + 2x(2x 5/10e)) for nurse call systems in hospitals, EPHADs, etc. With its blue halogen-free sheath, it is perfectly suited for public access areas.



ADVANTAGES

- RoHS compliant
- LSZH
- Cca s1d1a1

AXCITY
/ ADALTRA

CONSTRUCTION & TECHNICAL PERFORMANCE

Outer Sheath Material	LSZH
Color	Blue
Nom. diameter of the outer sheath (mm)	8.0

MECHANICAL CHARACTERISTICS

Bending Radius in Fixed Installation	8 x Ø ext
Bending Radius in Mobile Installation	15 x Ø ext

ENVIRONMENTAL CHARACTERISTIC

CPR classification	Cca s1, d1, a1
Fire behaviour	IEC 60332-1, IEC 60332-3-24, IEC 61034-1, IEC 61034-2, IEC 60754-1& 2

ORDER INFORMATION

REFERENCE	CONSTRUCTION	Ø SHEATH NOM (MM)	WEIGHT (KG/KM)
MDC2152P510SHC	2x1.5+2x2x5/10	8.0	145