

CE – Declaration of Conformity

Document: CE-UKCA230503C_Zip Pro
 Product Inspection: PI230502A
 Risk Assessment: RA230308A

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

Zip Pro

Name(s)

To which this declaration relates is in conformity with the following EC-directive(s):

<i>Directive 2014 / 30 / EU</i> Electromagnetic compatibility (EMC)	<i>Directive 2014 / 35 / EU</i> Low Voltage directive (LVD)	<i>Directive 2009 / 125 / EF</i> (Regs 244/2009, 245/2009, 347/2010)* Ecodesign requirements (ECO) <small>* As applicable and including amendments</small>
--	--	---

RoHS 2011 / 65 / EU + RoHS III / EU 2015/863

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-1:2021	(Luminaires – General purpose)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 60570:2003	(Luminaires - Electrical supply track systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)


CE declaration date: 2023

Statement of Conformity

issued by SG Armaturen AS

Manufacturer
Lillesand, 03/05-2023
 Place and date of issue

Martin Etrup
Approval Engineer
 Name of authorized person


Signature of authorized person

UKCA – Declaration of Conformity

Document: CE-UKCA230503C_Zip Pro
 Product Inspection: PI230502A
 Risk Assessment: RA230308A

We, **SG Armaturen AS**
Skytterheia 25
N-4790 Lillesand - Norway

declare under sole responsibility that the product

Luminaire

Type

Zip Pro

Name(s)

To which this declaration relates is in conformity with the following UK-regulations:

<i>UK SI 2016 No. 1091</i>	<i>UK SI 2016 No. 1101</i>	<i>UK SI 2010 No. 2617</i>	<i>UK SI 2012 No. 3032</i>
The Electromagnetic Compatibility Regulations 2010	The Electrical Equipment (Safety) Regulations 2016	The Ecodesign for Energy-Related Products Regulations 2010 Equipment (Safety) Regulations 2016	The Restriction of the Use of Certain Hazardous Substances in Electrical Equipment Regulations 2012

The conformity of the product with the provisions of the directives is stated by the compliance with the following standards:

EN 60598-1:2021+A11:2022	(Luminaires - General requirements)
EN 60598-2-1:2021	(Luminaires – General purpose)
EN 62471:2008	(Luminaires – Photobiological safety of lamps and lamp systems)
EN 60570:2003	(Luminaires - Electrical supply track systems)
EN 62493:2015	(EMF – Lighting equipment related to human exposure)
EN 55015:2019+A11:2020	(EMC - Radio disturbance)
EN 61000-3-2:2019	(EMC - Harmonics)
EN 61000-3-3:2013+A1:2019	(EMC – Voltage change, fluctuation & flicker)
EN 61547:2009	(EMC - Immunity)
UK SI 2021 No. 1095	(Luminaires – The Ecodesign for Energy-Related products and Energy Information)


UKCA declaration date: 2023

Statement of Conformity

issued by SG Armaturen AS

Manufacturer
Lillesand, 03/05-2023
 Place and date of issue

Martin Etrup
Approval Engineer
 Name of authorized person


Signature of authorized person

Declaration of Conformity statements/valid for the following products:

Product ID Number	Product Description	Article type	Article group
7021983207302	Zip Pro 3-Circuit White 3470lm	3000K Ra>90 DALI	702765
7021983207333	Zip Pro 3-Circuit Black 3610lm	4000K Ra>90 DALI	702765
7021983207326	Zip Pro 3-Circuit Black 3370lm	3000K Ra>90 DALI	702765
7021983207319	Zip Pro 3-Circuit White 3710lm	4000K Ra>90 DALI	702765
7021983207340	Zip Pro 3-Circuit White 40° 3470lm	3000K Ra>90 On/Off	701975
7021983207357	Zip Pro 3-Circuit White 40° 3710lm	4000K Ra>90 On/Off	701975
7021983207364	Zip Pro 3-Circuit Black 40° 3370lm	3000K Ra>90 On/Off	701975
7021983207371	Zip Pro 3-Circuit Black 40° 3610lm	4000K Ra>90 On/Off	701975
7021980034970	Zip Pro 3-Circuit Silver 40° 2840lm	4000K Ra>90 On/Off	701975