

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Lackspray NC
- **Article number:** REZ04
- **Relevant identified uses of the substance or mixture and uses advised against** Paintwork
- **Application of the substance / the preparation** Paintwork
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Peter Kwasny GmbH
Heilbronner Str. 96
D-74831 Gundelsheim
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** Tel.: +49 6269 95 20

Tel.: 0049-(0)6269-95-20
E-mail: labor@kwasny.de

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R18-66-67: In use, may form flammable/explosive vapour-air mixture. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 1)

Code letter and hazard designation of product:

Xi Irritant
F+ Extremely flammable

Risk phrases:

- 12 Extremely flammable.
- 18 In use, may form flammable/explosive vapour-air mixture.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe aerosol.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.

Classification in accordance with Directive 75/324/EEC: Extremely flammable

Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Xi R36; F R11 R66-67 ----- Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 106-97-8 EINECS: 203-448-7	butane F+ R12 R18 ----- Flam. Gas 1, H220; Press. Gas, H280	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane F+ R12 R18 ----- Flam. Gas 1, H220; Press. Gas, H280	5-10%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 ----- Flam. Liq. 3, H226; STOT SE 3, H336	5-10%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34-xxxx	xylene Xn R20/21; Xi R38 R10 Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2110475791-29-xxxx	2-methoxy-1-methylethyl acetate R10 Flam. Liq. 3, H226	2.5-5%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butan-1-ol Xn R22; Xi R37/38-41 R10-67 Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335+H336	1-2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media -**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Cool container with water
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Take note of emission threshold.
Use only in well ventilated areas.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone	
WEL ()	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
106-97-8 butane	
WEL ()	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
123-86-4 n-butyl acetate	
WEL ()	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
1330-20-7 xylene	
WEL ()	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
108-65-6 2-methoxy-1-methylethyl acetate	
WEL ()	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
71-36-3 butan-1-ol	
WEL ()	Short-term value: 154 mg/m ³ , 50 ppm Sk

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 4)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves** Nitrile rubber, NBR
- **Penetration time of glove material**
Gloves must be changed after every contamination.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
butyl rubber, 0,7mm
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
- **Flash point:**

Flash point:	< 0°C
	Without propellant gas.
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 365°C
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 5)

· Explosion limits:	
Lower:	1.5 Vol %
Upper:	13.0 Vol %
· Vapour pressure at 20°C:	3600 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	68.9 % With propellant gas. Content given by weight.
Solids content:	16.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Possible in traces.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Toxicity**
- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Empty aerosols can be disposed with the ordinary waste.

- **European waste catalogue**

15 01 10*	packaging containing residues of or contaminated by dangerous substances
-----------	--

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
not classified
- **UN-Number:** 1950
- **Packaging group:** -
not classified
- **Hazard label** 2.1
- **UN proper shipping name:** 1950 AEROSOLS
- **Limited quantities (LQ)** 1L
- **Transport category** 2
- **Tunnel restriction code** D

- **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
not classified
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 7)

· **Proper shipping name:** AEROSOLS· **Air transport ICAO-TI and IATA-DGR:**· **ICAO/IATA Class:** 2.1· **UN/ID Number:** 1950· **Label** 2.1· **Packaging group:** -
not classified· **Proper shipping name:** AEROSOLS, flammable· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1· **Special precautions for user** Warning: Gases.· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant

F+ Extremely flammable

· **Risk phrases:**

12 Extremely flammable.

18 In use, may form flammable/explosive vapour-air mixture.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

2 Keep out of the reach of children.

16 Keep away from sources of ignition - No smoking.

23 Do not breathe aerosol.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

· **Classification in accordance with Directive 75/324/EEC:** Extremely flammable· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	50-100

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.01.2012

Revision: 10.01.2012

Trade name: Lackspray NC

(Contd. of page 8)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
-
- R10 Flammable.
 R11 Highly flammable.
 R12 Extremely flammable.
 R18 In use, may form flammable/explosive vapour-air mixture.
 R20/21 Harmful by inhalation and in contact with skin.
 R22 Harmful if swallowed.
 R36 Irritating to eyes.
 R37/38 Irritating to respiratory system and skin.
 R38 Irritating to skin.
 R41 Risk of serious damage to eyes.
 R66 Repeated exposure may cause skin dryness or cracking.
 R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Product safety department

· **Contact:** Hr. Hamberger

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals

· *** Data compared to the previous version altered.**