




ENERG

енергия · ενεργεια




Midea

MHC-V18W/D2RN8



55°C

35°C



A⁺⁺

A⁺⁺⁺



-- dB



71dB

18
18
18
kW

18
18
18
kW



2019

811/2013

Midea

Product fiche 1

Heat pump space heater		unit	MHC-V18W/D2RN8	MHC-V22W/D2RN8	MHC-V26W/D2RN8	MHC-V30W/D2RN8
Indoor unit sound power (*)		[dB(A)]	/	/	/	/
Outdoor unit sound power (*)		[dB(A)]	71	73	75	77
Capacity of the back-up heater integrated in the unit	Psup back-up heater	[kW]	0	0	0	0
off peak operation function integrated in Heat pump		Y/N	No	No	No	No
Space heating	Energy efficiency class 35°C (Low temp. app.)	-	A+++	A+++	A+++	A++
Space heating	Energy efficiency class 55°C (Medium temp. app.)	-	A++	A++	A+	A+
Average climate (Design temperature= -10°C)						
Space heating 35°C	Prated(declared heating capacity) @-10°C	[kW]	18	22	25	29
	Seasonal space heating efficiency(ηs)	[%]	181	178	177	165
	Annual energy consumption	[kWh]	8,086	10,180	11,489	14,165
Space heating 55°C	Prated(declared heating capacity) @-10°C	[kW]	18	22	26	30
	Seasonal space heating efficiency(ηs)	[%]	125	126	123	123
	Annual energy consumption	[kWh]	11,375	14,390	17,204	19,316
Part load conditions space heating average climate low temperature application						
(A) condition (-7°C)	Pdh(declared heating capacity)	[kW]	15.91	19.73	22.15	21.95
	COPd (declared COP)	-	2.85	2.74	2.56	2.53
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (2°C)	Pdh(declared heating capacity)	[kW]	9.67	12.04	13.78	16.22
	COPd (declared COP)	-	4.57	4.40	4.41	4.12
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh(declared heating capacity)	[kW]	6.57	8.02	9.38	10.69
	COPd (declared COP)	-	5.95	6.24	6.43	6.21
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh(declared heating capacity)	[kW]	3.77	3.81	4.11	4.59
	COPd (declared COP)	-	6.97	7.0	7.08	7.14
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90

Product fiche 2

Heat pump space heater		unit	MHC-V18W/D2RN8	MHC-V22W/D2RN8	MHC-V26W/D2RN8	MHC-V30W/D2RN8
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	-10	-10	-10	-10
	Pdh (declared heating capacity)	[kW]	18.14	20.34	20.36	20.43
	COPd (declared COP)	-	2.49	2.35	2.34	2.34
	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60
(F) Tbivalent temperature	Tbiv	[°C]	-7	-7	-7	-5
	Pdh (declared heating capacity)	[kW]	15.91	19.73	22.15	23.57
	COPd (declared COP)	-	2.85	2.74	2.56	2.70
Supplementary capacity at P_design	Psup (@Tdesignh:-10°C)	[kW]	0.00	1.97	4.68	8.75
Part load conditions space heating average climate medium temperature application						
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	15.64	19.84	20.65	20.12
	COPd (declared COP)	-	1.72	1.74	1.69	1.63
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	9.62	11.91	14.28	16.50
	COPd (declared COP)	-	3.30	3.30	3.11	3.09
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	6.40	7.99	9.30	10.51
	COPd (declared COP)	-	4.41	4.62	4.72	4.73
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.60	3.62	3.90	4.65
	COPd (declared COP)	-	5.09	5.20	5.41	5.85
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	-10	-10	-10	-10
	Pdh (declared heating capacity)	[kW]	15.03	13.83	13.87	13.83
	COPd (declared COP)	-	1.17	1.08	1.08	1.07
	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60
(F) Tbivalent temperature	Tbiv	[°C]	-7	-7	-6	-5
	Pdh (declared heating capacity)	[kW]	15.64	19.84	22.13	23.98
	COPd (declared COP)	-	1.72	1.74	1.88	2.02
Supplementary capacity at P_design	Psup (@Tdesignh:-10°C)	[kW]	2.64	8.6	12.28	15.86

Product fiche 3

Heat pump space heater		unit	MHC-V18W/D2RN8	MHC-V22W/D2RN8	MHC-V26W/D2RN8	MHC-V30W/D2RN8
Colder climate (Design temperature = -22°C)						
Space heating 35°C	Prated (declared heating capacity) @ -22°C	[kW]	18	21	26	29
	Seasonal space heating efficiency (ηs)	[%]	146	146	143	138
	Annual energy consumption	[kWh]	11,740	14,179	17,421	20,390
Space heating 55°C	Prated (declared heating capacity) @ -22°C	[kW]	18	22	26	30
	Seasonal space heating efficiency (ηs)	[%]	97	102	101	100
	Annual energy consumption	[kWh]	18,156	21,067	24,967	29,238
Part load conditions space heating colder climate low temperature application						
condition (-15°C)	Pdh (declared heating capacity)	[kW]	14.49	17.46	18.95	18.61
	COPd (declared COP)	-	2.42	2.36	2.27	2.24
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	11.21	13.30	15.91	18.49
	COPd (declared COP)	-	3.09	3.12	3.10	3.07
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.64	8.25	10.10	11.88
	COPd (declared COP)	-	4.50	4.42	4.45	4.42
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.77	5.45	6.30	7.53
	COPd (declared COP)	-	5.85	5.87	6.06	6.15
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.95	3.98	4.03	4.11
	COPd (declared COP)	-	7.18	7.19	7.13	6.87
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	-22	-22	-22	-22
	Pdh (declared heating capacity)	[kW]	13.14	13.27	13.07	13.17
	COPd (declared COP)	-	1.67	1.69	1.67	1.67
	WTOL (Heating water Operation Limit)	[°C]	37	37	37	37
(F) Tbivalent temperature	Tbiv	[°C]	-15	-15	-12	-10
	Pdh (declared heating capacity)	[kW]	14.49	17.46	18.97	19.93
	COPd (declared COP)	-	2.42	2.36	2.36	2.44
Supplementary capacity at P_design	Psup (@Tdesignh:-22°C)	[kW]	4.62	8.13	12.68	15.96

Product fiche 4

Heat pump space heater		unit	MHC-V18W/D2RN8	MHC-V22W/D2RN8	MHC-V26W/D2RN8	MHC-V30W/D2RN8
Part load conditions space heating colder climate medium temperature application						
condition (-15°C)	Pdh (declared heating capacity)	[kW]	13.56	13.78	13.37	13.06
	COPd (declared COP)	-	1.21	1.24	1.20	1.18
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	11.12	13.53	15.90	18.40
	COPd (declared COP)	-	1.98	2.07	2.10	2.10
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.65	8.61	10.17	11.23
	COPd (declared COP)	-	3.44	3.70	3.58	3.51
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.66	5.21	6.52	7.42
	COPd (declared COP)	-	4.35	4.49	4.99	5.18
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.74	3.74	3.63	3.64
	COPd (declared COP)	-	5.68	5.76	5.68	5.73
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	-15	-15	-15	-15
	Pdh (declared heating capacity)	[kW]	13.56	13.78	13.37	13.06
	COPd (declared COP)	-	1.21	1.24	1.20	1.18
	WTOL (Heating water Operation Limit)	[°C]	50	50	50	50
(F) Tbivalent temperature	Tbiv	[°C]	-7	-7	-7	-7
	Pdh (declared heating capacity)	[kW]	11.12	13.53	15.90	18.40
	COPd (declared COP)	-	1.98	2.07	2.10	2.10
Supplementary capacity at P_design	Psup (@Tdesignh:-22°C)	[kW]	18.38	22.36	26.27	30.41
Warmer climate (Design temperature =2°C)						
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	18	22	26	30
	Seasonal space heating efficiency (ηs)	[%]	226	234	231	213
	Annual energy consumption	[kWh]	4,116	4,945	5,959	7,540
Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	18	22	26	30
	Seasonal space heating efficiency (ηs)	[%]	157	161	168	163
	Annual energy consumption	[kWh]	6,041	7,180	8,218	9,580

Product fiche 5

Heat pump space heater		unit	MHC-V18W/D2RN8	MHC-V22W/D2RN8	MHC-V26W/D2RN8	MHC-V30W/D2RN8
Part load conditions space heating warmer climate low temperature application						
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	17.84	21.81	25.50	26.29
	COPd (declared COP)	-	3.53	3.31	3.0	2.94
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	11.36	14.08	16.77	19.57
	COPd (declared COP)	-	5.16	5.20	5.02	4.75
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	5.45	6.44	7.65	8.90
	COPd (declared COP)	-	7.01	7.50	7.78	7.53
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	2	2	2	2
	Pdh (declared heating capacity)	[kW]	17.84	21.81	25.50	26.29
	COPd (declared COP)	-	3.53	3.31	3.0	2.94
	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60
(F) Tbivalent temperature	Tbiv	[°C]	7	7	7	7
	Pdh (declared heating capacity)	[kW]	11.36	14.08	16.77	19.57
	COPd (declared COP)	-	5.16	5.20	5.02	4.75
Supplementary capacity at P_design	Psup (@Tdesignh:2°C)	[kW]	0.00	0.09	0.58	4.15
Part load conditions space heating warmer climate medium temperature application						
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	18.44	22.12	26.50	26.41
	COPd (declared COP)	-	2.12	2.12	1.99	1.99
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	11.62	14.15	16.86	19.11
	COPd (declared COP)	-	3.49	3.50	3.47	3.37
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	5.35	6.38	7.58	8.92
	COPd (declared COP)	-	5.09	5.34	5.94	6.09
	Cdh(degradation coefficient)	-	0.90	0.90	0.90	0.90
(E) Tol(temperature operating limit)	Tol (temperature operating limit)	[°C]	2	2	2	2
	Pdh (declared heating capacity)	[kW]	18.44	22.12	26.50	26.41
	COPd (declared COP)	-	2.12	2.12	1.99	1.99
	WTOL (Heating water Operation Limit)	[°C]	60	60	60	60

Product fiche 6

Heat pump space heater		unit	MHC-V18W/D2RN8	MHC-V22W/D2RN8	MHC-V26W/D2RN8	MHC-V30W/D2RN8
(F) Tbivalent temperature	Tbiv	[°C]	7	7	7	7
	Pdh (declared heating capacity)	[kW]	11.62	14.15	16.86	19.11
	COPd (declared COP)	-	3.49	3.50	3.47	3.37
Supplementary capacity at P_design	Psup (@Tdesignh:2°C)	[kW]	0.00	0.00	0.00	3.32
Ecodesign technical data						
Product description	Air-to-water heat pump	Y/N	Yes	Yes	Yes	Yes
	Water-to-water heat pump	Y/N	No	No	No	No
	Brine-to-water heat pump	Y/N	No	No	No	No
	Low-temperature heat pump	Y/N	No	No	No	No
	Equipped with a supplementary heater	Y/N	No	No	No	Yes
	Heat pump combination heater	Y/N	No	No	No	No
Air to water unit	Rated airflow (outdoor)	[m³/h]	10650	10650	11200	11200
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m³/h]	/	/	/	/
Other	Capacity control	-	Inverter	Inverter	Inverter	Inverter
	Poff (Power consumption Off mode)	[kW]	0.018	0.018	0.018	0.018
	Pto (Power consumption Thermostat off mode)	[kW]	0.096	0.096	0.096	0.096
	Psb (Power consumption Standby mode)	[kW]	0.018	0.018	0.018	0.018
	PCK (Power crankcase heater model)	[kW]	0.000	0.000	0.000	0.000
	Qelec (Daily electricity consumption)	[kWh]	/	/	/	/
	Qfuel (Daily fuel consumption)	[kWh]	/	/	/	/
Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.						
Product fiche data according to energy label directive 2010/30/EC regulation (EU) 811/2013.						

Technical parameters

Model(s):	MHC-V18W/D2RN8
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	AVERAGE

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	17.7	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	15.6	kW
Tj = 2 °C	Pdh	9.6	kW
Tj = 7 °C	Pdh	6.4	kW
Tj = 12 °C	Pdh	3.6	kW
Tj = bivalent temperature	Pdh	15.6	kW
Tj = operating limit	Pdh	15.0	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	Pcyc	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	Poff	0.018	kW
Standby mode	Psb	0.018	kW
Thermostat-off mode	Pto	0.096	kW
Crankcase heater mode	Pck	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	LWA	-71	dB
Annual energy consumption	QHE	11375	kWh

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	ηs	125	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COPd	1.72	-
Tj = 2 °C	COPd	3.30	-
Tj = 7 °C	COPd	4.41	-
Tj = 12 °C	COPd	5.09	-
Tj = bivalent temperature	COPd	1.72	-
Tj = operating limit	COPd	1.17	-
For air-to-water heat pumps: Tj = -15 °C	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval efficiency	COPcyc	-	-
Heating water operating limit temperature	WTOL	60	°C
Supplementary heater			
Rated heat output (**)	Psup	2.6	kW
Type of energy input	Electrical		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m³/h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Qclec	-	kWh
Annual electricity consumption	AEC	-	kWh
Water heating energy efficiency	ηwh	-	%
Daily fuel consumption	Qfuel	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details	GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)
-----------------	--

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Technical parameters

Model(s):	MHC-V18W/D2RN8
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	COLDER
Parameters are declared for medium-temperature application.	

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	18.4	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	11.1	kW
Tj = 2 °C	Pdh	6.7	kW
Tj = 7 °C	Pdh	4.7	kW
Tj = 12 °C	Pdh	3.7	kW
Tj = bivalent temperature	Pdh	11.1	kW
Tj = operating limit	Pdh	13.6	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	13.6	kW
Bivalent temperature	Tbiv	-7	°C
Cycling interval capacity for heating	Pcyc	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	Poff	0.018	kW
Standby mode	Psb	0.018	kW
Thermostat-off mode	Pto	0.096	kW
Crankcase heater mode	Pck	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	LWA	-71	dB
Annual energy consumption	QHE	18156	kWh

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Qelec	-	kWh
Annual electricity consumption	AEC	-	kWh
Water heating energy efficiency	η_{wh}	-	%
Daily fuel consumption	Qfuel	-	kWh
Annual fuel consumption	AFC	-	GJ

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	97	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COPd	1.98	-
Tj = 2 °C	COPd	3.44	-
Tj = 7 °C	COPd	4.35	-
Tj = 12 °C	COPd	5.68	-
Tj = bivalent temperature	COPd	1.98	-
Tj = operating limit	COPd	1.21	-
For air-to-water heat pumps: Tj = -15 °C	COPd	1.21	-
For air-to-water heat pumps: Operation limit temperature	TOL	-15	°C
Cycling interval efficiency	COPcyc	-	-
Heating water operating limit temperature	WTOL	50	°C
Supplementary heater			
Rated heat output (**)	Psup	18.4	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m³/h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h

Contact details	GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)
-----------------	--

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Technical parameters

Model(s):	MHC-V18W/D2RN8
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	WARMER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	18.1	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	-	kW
Tj = 2 °C	Pdh	18.4	kW
Tj = 7 °C	Pdh	11.6	kW
Tj = 12 °C	Pdh	5.4	kW
Tj = bivalent temperature	Pdh	11.6	kW
Tj = operating limit	Pdh	18.4	kW
For air-to-water heat pumps: Tj = -15 °C	Pdh	-	kW
Bivalent temperature	Tbiv	7	°C
Cycling interval capacity for heating	Pcyc	-	kW
Degradation co-efficient (**)	Cdh	0.9	--
Power consumption in modes other than active mode			
Off mode	Poff	0.018	kW
Standby mode	Psb	0.018	kW
Thermostat-off mode	Pto	0.096	kW
Crankcase heater mode	Pck	0.000	kW

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	LWA	-71	dB
Annual energy consumption	QHE	6041	kWh

For heat pump combination heater:

Declared load profile	-			Water heating energy efficiency	η_{wh}	-	%
Daily electricity consumption	Qelec	-	kWh	Daily fuel consumption	Qfuel	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ

Contact details	GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)		
-----------------	--	--	--

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	157	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	COPd	-	-
Tj = 2 °C	COPd	2.12	-
Tj = 7 °C	COPd	3.49	-
Tj = 12 °C	COPd	5.09	-
Tj = bivalent temperature	COPd	3.49	-
Tj = operating limit	COPd	2.12	-
For air-to-water heat pumps: Tj = -15 °C	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COPcyc	-	-
Heating water operating limit temperature	WTOL	60	°C
Supplementary heater			
Rated heat output (**)	Psup	0.0	kW
Type of energy input	-		

For air-to-water heat pumps: Rated air flow rate, outdoors	-	10650	m³/h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h

Information requirements for comfort chillers

Model(s):				MHC-V18W/D2RN8				
Outdoor side heat exchanger of chiller:				Air to water				
Indoor side heat exchanger chiller:				Water				
Type:				Compressor driven vapour compression				
Driver of compressor:				Electric motor				
Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated cooling capacity	P _{rated,c}	16.6	kW		Seasonal space cooling energy efficiency	η _{s,c}	185	%
Declared cooling capacity for part load at given outdoor temperature T _j					Declared energy efficiency ratio for part load at given outdoor temperature T _j			
T _j =+35°C	P _{dc}	16.6	kW		T _j =+35°C	EER _d	3.06	-
T _j =+30°C	P _{dc}	11.9	kW		T _j =+30°C	EER _d	4.13	-
T _j =+25°C	P _{dc}	7.6	kW		T _j =+25°C	EER _d	5.59	-
T _j =+20°C	P _{dc}	3.5	kW		T _j =+20°C	EER _d	5.55	-
Degradation co-efficient for chillers (*)	C _{dc}	0.9	-					
Power consumption in modes other than "active mode"								
Off mode	P _{OFF}	0.017	kW		Crankcase heater mode	P _{CK}	0.000	kW
Thermosat-off mode	P _{TO}	0.084	kW		Standby mode	P _{SB}	0.017	kW
Other items								
Capacity control	variable				For air-to-water comfort chillers: air flow rate, outdoor measured	-	8100	m³/h
Sound power level, indoors / outdoors	L _{WA}	-71	dB		For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	m³/h
Emissions of nitrogen oxides (if applicable)	NO _x (**)	-	mg/kWh input GCV					
GWP of the refrigerant	-	675	kg CO ₂ eq (100years)					
Standard rating conditions used		Low temperature application						
Contact details		GD Midea Heating & Ventilating Equipment Co. , Ltd. Penglai industry Road, Beijiao, Shunde, Foshan, Guangdong, 528311 P.R. China						

(*) If C_{dc} is not determined by measurement then the default degradation coefficient of chillers shall be 0,9.
(**) From 26 September 2018.

Information requirements for comfort chillers

Model(s):				MHC-V18W/D2RN8			
Outdoor side heat exchanger of chiller:				Air to water			
Indoor side heat exchanger chiller:				Water			
Type:				Compressor driven vapour compression			
Driver of compressor:				Electric motor			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	18.4	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	216	%
Declared cooling capacity for part load at given outdoor temperature T_j				Declared energy efficiency ratio for part load at given outdoor temperature T_j			
$T_j=+35^{\circ}\text{C}$	P_{dc}	18.4	kW	$T_j=+35^{\circ}\text{C}$	EER_d	4.44	-
$T_j=+30^{\circ}\text{C}$	P_{dc}	13.3	kW	$T_j=+30^{\circ}\text{C}$	EER_d	5.26	-
$T_j=+25^{\circ}\text{C}$	P_{dc}	8.5	kW	$T_j=+25^{\circ}\text{C}$	EER_d	6.68	-
$T_j=+20^{\circ}\text{C}$	P_{dc}	3.3	kW	$T_j=+20^{\circ}\text{C}$	EER_d	5.15	-
Degradation co-efficient for chillers (*)	C_{dc}	0.9	-				
Power consumption in modes other than "active mode"							
Off mode	P_{OFF}	0.017	kW	Crankcase heater mode	P_{CK}	0.000	kW
Thermosat-off mode	P_{TO}	0.084	kW	Standby mode	P_{SB}	0.017	kW
Other items							
Capacity control	variable			For air-to-water comfort chillers: air flow rate, outdoor measured	-	8100	m^3/h
Sound power level, indoors / outdoors	L_{WA}	-71	dB				
Emissions of nitrogen oxides (if applicable)	NO_x (**)	-	mg/kWh input GCV	For water / brine-to-water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-	-	m^3/h
GWP of the refrigerant	-	675	kg CO_2 eq (100years)				
Standard rating conditions used		Medium temperature application					
Contact details		GD Midea Heating & Ventilating Equipment Co. , Ltd. Penglai industry Road, Beijiao, Shunde, Foshan, Guangdong, 528311 P.R. China					

(*) If C_{dc} is not determined by measurement then the default degradation coefficient of chillers shall be 0,9.
(**) From 26 September 2018.

Model	Mode	Heating					Cooling	
	Ambient temperature	7/6			2/1	-7/-8	35/24	
	Water temperature	30-35	40-45	47-55	30-35	30-35	23-18	12-7
MHC-V18W/D2RN8	Capacity /W	18000	18000	18000	18000	18000	18500	17000
	Power input /W	3830	5143	6545	5325	6667	3895	5574
	COP / EER	4.70	3.50	2.75	3.38	2.70	4.75	3.05
MHC-V22W/D2RN8	Capacity /W	22000	22000	22000	22000	21000	23000	21000
	Power input /W	5000	6471	8302	7097	8077	5000	7119
	COP / EER	4.40	3.40	2.65	3.10	2.60	4.60	2.95
MHC-V26W/D2RN8	Capacity /W	26000	26000	26000	24000	22000	27000	26000
	Power input /W	6373	8387	10612	8333	8800	6279	9630
	COP / EER	4.08	3.10	2.45	2.88	2.50	4.30	2.70
MHC-V30W/D2RN8	Capacity /W	30100	30000	30000	26000	23000	31000	29500
	Power input /W	7698	10345	13043	9286	9388	7750	11569
	COP / EER	3.91	2.90	2.30	2.80	2.45	4.00	2.55