



## ZODZ2.E66583 Positioning Devices - Component

Page Bottom

### Positioning Devices - Component

[See General Information for Positioning Devices - Component](#)

#### BOCCHIOTTI SPA

E66583

VIA VITTOR PISANI 16  
20124 MILANO, MI ITALY

**PVC ducts**, TD Series^; Cat. No. TD followed by 25x25, 25x50, 37.5x25, 37.5x50, 37.5x75, 50x37.5, 50x50, 50x75, 75x50, 75x75, 75x125, 100x50, 100x75, 100x125, 125x50, 125x75, suffixed by "G", grey color. Rated 50°C.

**PVC ducts**, T1 Series^; Cat. No. T1 followed by 15x18, 15x30, 15x40, 15x60, 25x30, 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 75x125, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 100x125, 120x60, 120x80, 150x100, suffixed with the letter "G" denoting color grey, "W" denoting color white, "BL" denoting color blue, or "A" denoting color black. Rated 50°C.

**PVC ducts**, T1-E Series^; Cat. No. T1-E followed by 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 120x60, 120x80, 150x100, suffixed with the letter "G" denoting color grey, "W" denoting color white, or "A" denoting color black. Rated 50°C.

**PVC ducts**, T1-EF Series^; Cat. No. T1-EF followed by 25x80, 25x100, 40x80, 40x100, 60x80, 60x100, 80x80, 80x100, 100x80, 100x100, 120x60, 120x80, 150x100, suffixed with the letter "G" denoting color grey, "W" denoting color white, "BL" denoting color blue or "A" denoting color black. Rated 50°C.

**PVC ducts**, T1-F Series^; Cat. No. T1F followed by 25x80, 25x100, 40x80, 40x100, 60x80, 60x100, 80x80, 80x100, 100x80, 100x100, 120x60, 120x80, 150x100, suffixed with the letter "G" denoting color grey, "W" denoting color white, "BL" denoting color blue or "A" denoting color black. Rated 50°C.

**PVC ducts**, T1-N Series^; Cat. No. T1-N followed by 25x30, 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 120x60, 120x80, 150x100, suffixed by "G", grey color. Rated 50°C.

**PVC ducts**, T1-EN Series^; Cat. No. T1-N followed by 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 120x60, 120x80, suffixed by "G", grey color. Rated 50°C.

**PVC ducts**, TS-H Series^; Cat. No. TS-H followed by 15x18, 15x30, 25x30, 25x40, 25x80, 40x40, 40x60, 40x80, 60x60, 60x80, 80x60, 80x80, 80x100, 100x80, 100x100, suffixed by "G", color grey. Rated 50°C.

**PVC ducts**, TS Series^; Cat. No. TS followed by 15x18, 15x30, 25x30, 25x40, 25x80, 40x40, 40x60, 40x80, 60x60, 60x80, 80x60, 80x80, 80x100, 100x80, 100x100, suffixed by "G", color grey. Rated 50°C.

**PVC ducts**, Cat. Nos. Open T1-H 25x37.5 LG, T1-H 25x50 LG, T1-H 25x75 LG, T1-H 37.5x37.5 LG, T1-H 37.5x50 LG, T1-H 37.5x75 LG, T1-H 50x50 LG, T1-H 50x75 LG, T1-H 50x100 LG, T1-H 75x50 LG, T1-H 75x75 LG, T1-H 75x100 LG, T1-H 100x50 LG, T1-H 100x75 LG, T1-H 100x100 LG, Light Grey. Rated 50°C.

**PVC ducts**, Cat. Nos. Narrow T1-EH 37.5x37.5 LG, T1-EH 37.5x50 LG, T1-EH 37.5x75 LG, T1-EH 50x50 LG, T1-EH 50x75 LG, T1-EH 50x100 LG, T1-EH 75x50 LG, T1-EH 75x75 LG, T1-EH 75x100 LG, T1-EH 100x50 LG, T1-EH 100x75 LG, T1-EH 100x100 LG, rated 50C. Light Grey color.

**PP Slotted flexible ducts**%, designated "DINOSAURO" Series^, Cat. Nos. DN-10A W, DN-20A W, DN-30A W, DN-40A W, DN-A 25 W, DN-A 35 W, DN-A 45 W, grey color. Rated 80°C.

**PP ducts**^, Cat. Nos. DN-A 25G or DN-AS, DN-A 35G or DN-AM, DN-A 45G and DN-AL, gray color. Rated 65°C.

**PVC Slotted ducts**, T1-D Series^; Cat. Nos. T1-D 25x40 G, -25x60 G, -25x80 G; T1-D 40x40 G, -40x60 G, -40x80 G, 40x100 G; T1-D 60x40 G, -60x60 G, -60x80 G, -60x100 G; T1-D 80x60 G, -80x80 G, -80x100 G; T1-D 100x60 G, -100x80 G, -100x100 G; T1-D 120x80 G, grey color. Rated 50°C.

% - The Beiersdorf double sided tape designated "Tesa 4965" may be used as the sole means of securement when it is used to affix these cable ducts to enamel painted metal and cellulose sheet impregnated with phenolic and melamine resins type surfaces.

^ - Ducts use raw materials rated minimum 94V-0. Ducts with handling strips use materials rated minimum 94V-0 for the ducts and 94V-2 for the handling strips. Ducts DN-A 25G, DN-AS, DN-A 35G, DN-AM, DN-A 45G and DN-AL use raw materials rated minimum 94V-2.



Marking: Company name, file number "E66583" or trademark , Cat. No. number of wires for maximum fill, the statement "For use within enclosures only" or the Recognition mark, and factory identification if applicable, on the product or smallest unit package.

Last Updated on 2013-01-23

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".