171.192

PDA-B1000 Professional Amplifier

Amplifiers for professional use fitted with strong front panels. Very versatile due to high power reserves and temperature controlled cooling fans. A robust construction suitable for heavy duty usage : DJ's, fixed installations and live performance.

Product colour : Black
Output channels : 2
Output power: RMS @ 4 Ohm per channel : 500W
Output power: RMS @ 8 Ohm per channel : 350W
Output power: RMS @ 8 Ohm bridged : 1000W
Input connections : Jack 6,35 mm, XLR 3 points
Output connections : NL-4
Frequency response : 10Hz - 50.000Hz
Crosstalk : >70dB
Signal-to-noise ratio : >100dB
Damping Factor : >350
Slew rate : 45V/uS
Input sensitivity line : 775mV - 1.2V
Input impedance : 20 kOhm
Power supply : 220-240VAC 50Hz
Dimensions (L x W x H) : 482 x 100 x 330mm (19" x2U)
Is the item 19"? : Yes
Weight (kg) : 10,90

- Puissance élevée, qualité sonore excellente
- Fonction démarrage souple et limiteur Clip
- Protection contre les courts-circuits, surcharges et surchauffes
- LED pour Signal, Clip et Protect pour chaque canal
- Fonctionnement mode stéréo et bridgé
- Affichage LCD bleu
- Refroidisseur innovant avec ventilateurs régulateurs de température
- Pour montage en rack 19“ (2 U)