

Motor cable, 2m, halogen free, for RAMO



Part no. **RAMO-CM1-2M0**
164282

Product name	Eaton Moeller® series Rapid Link Accessory Motor cable
Part no.	RAMO-CM1-2M0
EAN	4015081608126
Product Length/Depth	350 millimetre
Product height	70 millimetre
Product width	400 millimetre
Product weight	0.5 kilogram
Certifications	DIN VDE 0110 EN 61684 IEC/EN 60529
Product Tradename	Rapid Link
Product Type	Accessory
Product Sub Type	Motor cable
Enclosure material	Polycarbonate
Features	8 x 1.5 mm ² Halogen free Plastic plug
Functions	For connecting the motor starter to the motor
Locking facility	Material of locking facility: Polyamide (PA)
Material	Outer casing halogen free Polycarbonate Cable: Copper (Cu) flexible according to VDE 0295 Class 5
RAL-number	7001
Accessory/spare part type	Cable
Degree of protection	IP65, according to IEC/EN 60529
Flammability characteristics	Flame retardance, fire propagation: according to EN 50265-2-1
Terminal capacity	Conductor cross-section, Contact pins: 8 x 1.5 mm ² , Metal housing with plug-in connection 8 x 1.5 mm ² , Connection cable
Used with	RAMO
Environmental resistance	VDE 0472 Part 803 B (Resistance to oils and acids)
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	70 °C
Contact material	Silver-plated copper
Outer cable diameter	9 - 13 mm
Permitted bending radius	6 x outer cable diameter
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.

10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for frequency controller (EC002025)			
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter (accessory) (ecl@ss10.0.1-27-02-31-92 [AFR303003])			
Type of accessory/spare part			Cable
Accessory			Yes
Spare part			No