

Fuse-link, low voltage, 30 A, AC 600 V, DC 300 V, 300 kA, 26 x 29 x 55 mm,
CF, J, 1P, UL, CSA, non-indicating, finger-safe, time-delay

Part no. CUBEFUSE, TCF 30A NON-IND
Catalog No. TCF30RN

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	30
Rated voltage			AC 600 V DC 300 V
Size			26 x 29 x 55 mm
Utilization category			CF J
Status indicator			non-indicating
Description			finger-safe
Breaking Capacity		kA	300
Number of poles			1P
usable for size/applications			protection of wind power systems
Release characteristic	class		time-delay
Standard/Approval			UL CSA
Standards/Regulations			UL Listed CSA Certified
Time delay			time-delay 10 seconds (minimum) at 500% of rated current

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	30
Rated voltage		V	600
Voltage type			
Rated switching capacity		kA	
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_9000_TCF_TCF_RN.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/class_cf_cubefuse/tcf_tcf-rn_fuse_tcfh-nholder.html