

# ALIMENTATION LED INTÉRIÈRE

en tension constante 24V DC courant continu polarisé

## Alimentations extra-plates

P (w)	IP	Code
7,2	20	<b>52003</b>

L x l x h = 118 x 40 x 10 mm



P (w)	IP	Code
20	20	<b>52005</b>

L x l x h = 160 x 40 x 14 mm

P (w)	IP	Code
30	20	<b>52012</b>

L x l x h = 246 x 30 x 16 mm

## Alimentations

P (w)	IP	Code
12	20	<b>0697</b>

L x l x h = 80 x 40 x 27 mm



P (w)	IP	Code
30	20	<b>0632</b>

L x l x h = 150 x 40 x 30 mm

P (w)	IP	Code
50	20	<b>0675</b>
75	20	<b>52010</b>

L x l x h = 180 x 60 x 30 mm

P (w)	IP	Code
100	20	<b>0685</b>

L x l x h = 180 x 90 x 35 mm



P (w)	IP	Code
150	20	<b>0732</b>

L x l x h = 270 x 65 x 42 mm

Pour installation hors plafond.



P (w)	IP	Code
<b>N</b> 300	20	<b>52013</b>

L x l x h = 215 x 115 x 50 mm

## Appareils fonctionnant en 24V DC

MEUBLED



FOCUS R60



EGO



BOLO



SLIMLED  
KIT SLIMLED



LINCUS



JAKLED 30/60/65/120



MODULED 24



FLEXI CRISTAL 30/60/120  
FLEXO LED 30/60/65/120



Système changement de couleur RGB

JAKLED 65 RGB



METEOR  
MINI METEOR

