


# ELMA



Corps aluminium blanc/Réflecteur à facettes.  
Alimentation intégrée.  
Montage sur rail 1 ou 3 allumages.

	1 LED	7,5W	$\angle 36^\circ$
	230V	IP20	IK02 650°C 30 000 h
Fixation	Lumens	Teinte	Code
<b>N</b> rail	530	3000 K	<b>50466</b>
<b>N</b> 1 allum. (p.483)	570	4000 K	<b>50440</b>
<b>N</b> rail	530	3000 K	<b>50465</b>
<b>N</b> 3 allum. (p.485)	570	4000 K	<b>50439</b>



ELMA	3000 K	7,5 W	36°
	h (m)	E <sub>max</sub> (lx)	d (m)
	1	1361	0,65
	2	340	1,3
	3	151	1,9


ELMA	4000 K	7,5 W	36°
	h (m)	E <sub>max</sub> (lx)	d (m)
	1	1464	0,65
	2	366	1,3
	3	163	1,9

# ELMA PATÈRE



Corps aluminium blanc/Réflecteur à facettes.  
Alimentation intégrée. Fixation patère murale.

	1 LED	7,5W	$\angle 36^\circ$
	230V	IP20	IK02 650°C 30 000 h
Fixation	Lumens	Teinte	Code
<b>N</b> patère	530	3000 K	<b>50467</b>
<b>N</b> patère	570	4000 K	<b>50468</b>



ELMA	3000 K	7,5 W	36°
	h (m)	E <sub>max</sub> (lx)	d (m)
	1	1361	0,65
	2	340	1,3
	3	151	1,9

ELMA	4000 K	7,5 W	36°
	h (m)	E <sub>max</sub> (lx)	d (m)
	1	1464	0,65
	2	366	1,3
	3	163	1,9