

Editeur (trice) ARIC
Téléphone
Fax
Email

ARIC 50799 DALLE LED 600x600 36W 4000K UGR 19 24mm / Table UGR

Luminaire: ARIC 50799 DALLE LED 600x600 36W 4000K UGR 19 24mm

Lampes: 1 x LED

Evaluation éblouissement selon UGR											
ρ Plafond		70	70	50	50	30	70	70	50	50	30
ρ Murs		50	30	50	30	30	50	30	50	30	30
ρ Sol		20	20	20	20	20	20	20	20	20	20
Taille pièce X Y		Visée perpendiculaire vers axe des lampes					Visée longitudinale vers axe des lampes				
2H	2H	14.6	15.7	15.0	16.0	16.2	14.6	15.7	15.0	16.0	16.2
	3H	15.4	16.3	15.7	16.6	17.0	15.4	16.3	15.7	16.6	17.0
	4H	15.9	16.8	16.3	17.2	17.5	15.9	16.8	16.3	17.2	17.5
	6H	16.5	17.4	16.9	17.7	18.1	16.5	17.4	16.9	17.7	18.1
	8H	16.8	17.6	17.2	18.0	18.4	16.8	17.6	17.2	18.0	18.4
	12H	17.0	17.8	17.5	18.2	18.6	17.0	17.8	17.5	18.2	18.6
4H	2H	14.8	15.8	15.2	16.1	16.4	14.8	15.8	15.2	16.1	16.4
	3H	15.9	16.6	16.3	17.0	17.4	15.9	16.6	16.3	17.0	17.4
	4H	16.7	17.3	17.1	17.7	18.2	16.7	17.3	17.1	17.7	18.2
	6H	17.5	18.1	18.0	18.5	19.0	17.5	18.1	18.0	18.5	19.0
	8H	17.9	18.4	18.3	18.8	19.3	17.9	18.4	18.3	18.8	19.3
	12H	18.2	18.6	18.7	19.1	19.6	18.2	18.6	18.7	19.1	19.6
8H	4H	17.0	17.5	17.5	18.0	18.4	17.0	17.5	17.5	18.0	18.4
	6H	18.0	18.5	18.5	18.9	19.5	18.0	18.5	18.5	18.9	19.5
	8H	18.5	18.9	19.0	19.4	19.9	18.5	18.9	19.0	19.4	19.9
	12H	18.9	19.3	19.5	19.8	20.4	18.9	19.3	19.5	19.8	20.4
12H	4H	17.0	17.5	17.5	18.0	18.5	17.0	17.5	17.5	18.0	18.5
	6H	18.1	18.5	18.7	19.0	19.6	18.1	18.5	18.7	19.0	19.6
	8H	18.7	19.0	19.2	19.5	20.1	18.7	19.0	19.2	19.5	20.1
Variation de position de l'observateur pour écartement S entre luminaires											
S = 1.0H		+0.3 / -0.4					+0.3 / -0.4				
S = 1.5H		+0.7 / -0.7					+0.7 / -0.7				
S = 2.0H		+1.4 / -1.1					+1.4 / -1.1				
Tableau standard		BK06					BK06				
Nombre à ajouter pour la correction		1.3					1.3				
Indice d'éblouissement en fonction du 3850lm Flux lumineux total											

Les valeurs UGR sont calculées conformément à CIE Publ. 117. Spacing-to-Height-Ratio = 0.25.