



KIT TIPO R 230 LED 10



Corps aluminium. Orientable. Kit prêt-à-posser. **LED SHARP.**

QPAR 16	LED 3 SHARP	GU10	10W
230V	IP20	IK02	850° 35 000 h



Lumens	Teinte	Couleur	Code avec lampe
700	2700 K	blanc	51009
750	4000 K	blanc	51010
700	2700 K	alu. brossé	51011
750	4000 K	alu. brossé	51012

Dimmable avec variateur universel.
Lampe de rechange 2700 K, code **2952**.
4000 K, code **2953**.

LED 10	2700 K	10 W	38°
h (m)	E _{max} (lx)	d (m)	
1	1650	0,69	
2	413	1,4	
2,5	264	1,7	

LED 10	4000 K	10 W	38°
h (m)	E _{max} (lx)	d (m)	
1	1890	0,69	
2	473	1,4	
3	210	2,1	

KIT TIPO C 230 LED 10



Corps aluminium. Orientable. Kit prêt-à-posser. **LED SHARP.**

QPAR 16	LED 3 SHARP	GU10	10W
230V	IP20	IK02	850° 35 000 h

Lumens	Teinte	Couleur	Code avec lampe
700	2700 K	blanc	51050
750	4000 K	blanc	51051
700	2700 K	alu. brossé	51052
750	4000 K	alu. brossé	51053

Dimmable avec variateur universel.
Lampe de rechange 2700 K, code **2952**.
4000 K, code **2953**.

LED 10	2700 K	10 W	38°
h (m)	E _{max} (lx)	d (m)	
1	1650	0,69	
2	413	1,4	
2,5	264	1,7	

LED 10	4000 K	10 W	38°
h (m)	E _{max} (lx)	d (m)	
1	1890	0,69	
2	473	1,4	
3	210	2,1	



ENCASTRÉ