

# CE

Class C( $\geq$ 50% load)

## **Declaration of Conformity**

For the following equipment :

Product Name: Switching Power Supplies

Model Designation: HLG-320H-yz (y=12,15,20,24,30,36,42,48,54 ; z=A or B or Blank or C or D) is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied :

### RoHS Directive (2011/65/EU)

Energy-Related Products Directive (2009/125/EC) Implementing measure COMMISSION REGULATION(EC) No 1194/2012

#### Low Voltage Directive (2014/35/EU) :

EN61347-1:2008+A1+A2/EN61347-2-13:2006 EN61347-1:2008+A1+A2/EN61347-2-13:2006 TUV certificate No : R50210986 (for z=A,B,Blank,D type) TUV certificate No : R50211579 (for z=C type)

#### Electromagnetic Compatibility Directive (2014/30/EU):

#### **EMI (Electro-Magnetic Interference)**

Harmonic current

Conducted emission / Radiated emission

EN55015:2013+A1:2015

EN61000-3-2:2014

Voltage flicker EN61000-3-3: 2013

#### EMS (Electro-Magnetic Susceptibility)

EN61547:2009			
ESD air	EN61000-4-2:2009	Level 3	8KV
ESD contact	EN61000-4-2:2009	Level 2	4KV
RF field susceptibility	EN61000-4-3:2006+A1:2008+A2:2010	Level 2	3V/m
EFT bursts	EN61000-4-4:2012	Level 2	1KV/5KHz
Surge susceptibility	EN61000-4-5:2014	Level 4	2KV/Line-Line
Surge susceptibility	EN61000-4-5:2014	Level 4	4KV/Line-Earth
Conducted susceptibility	EN61000-4-6:2014	Level 2	3V
Magnetic field immunity	EN61000-4-8:2010	Level 2	3A/m
Valtage dia interruption	ENG1000 4 11:2004 . 05% dia 0 5 pariada	200/ dia 25	pariada - 05% interruptions 250 pariado

Voltage dip, interruption EN61000-4-11:2004 >95% dip 0.5 periods 30% dip 25 periods >95% interruptions 250 periods Note:

Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again. Tests above are only to be performed with intended loads, i.e. either with LEDs or resistive load. For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains.

This Declaration is effective from serial number RB6xxxxxxx

Person responsible for marking this declaration :

(Place)

MEAN WELL Enterprises Co., Ltd.						
(Manufacturer Name)						
No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 248, Taiwan						
(Manufacturer Address)	1		MADO			
Johnny Huang/Manager, Certification Center :	John	Ted Cheng/Director, Sales Dept. :	Leil Cherry			
(Name / Position)	(Signature)	(Name / Position)	(Signature)			
Taiwan	Oct. 28th. 2016					

(Date)