




## Photo



## Descriptions

This product is an adapter which inputs the incoming signals from an open/close switch to the air conditioner.

## Applicable Models


- MSZ-RW25,35,50VG
- MSZ-LN18,25,35,50,60VG2W,V,B,R
- MSZ-FT25,35,50VG
- MSZ-AP15,20VG
- MSZ-AP25,35,42,50,60,71VG
- MSZ-EF18,22,25,35,42,50VGW,B,S
- MSZ-BT20,25,35,50VG
- MSZ-HR25,35,42,50,60,71VF
- MSZ-DW25,35,50VF
- MSY-TP35,50VF
- MSZ-FH25,35,50VE2
- MSZ-WN25,35VA
- MSZ-DM25,35VA
- MSZ-HJ25,35,50,60,71VA
- MFZ-KT25,35,50,60VG
- MFZ-KW25,35,50,60VG
- MLZ-KP25,35,50VF

## Specifications

Model name		MAC-1702RA-E	MAC-1710RA-E
Size	Length	2 m	10 m
	Diameter	4.48 mm x 3.09 mm	4.48 mm x 3.09 mm
Material	Cable core	Tinned annealed copper wire	Tinned annealed copper wire
	Insulation	Heat-resistant PVC	Heat-resistant PVC
	Sheath	Heat-resistant PVC	Heat-resistant PVC
Weight		72 g	360 g
Standards	Standards	UL2464	UL2464
	Name	2464 2CFB #23	2464 2CFB #23

### Accessory

	Part name	Illustration	Q'ty
①	Mounting cord clamp ※		2
②	Screw for mounting 4×16		1
③	Fastener (for bundling the wires)		1




## How to Use / How to Install

### Card key/Window connection with the open/close switch

#### 1. How to connect the open/close switch

- Connect the connector to CN104 on the indoor electronic control P.C. board.
- Connect the electrical wires with the tag of "IN" to the switch.
- Separately insulate the wires with the tag of "OUT".



#### 2. Operation details


- Opening the switch stops operation of the air conditioner.  
A remote controller is enabled even the switch is open. To disable the remote controller, cut JR88 on the indoor electronic control P.C. board.
- When the switch closes, the ON/OFF operation from the remote controller is enabled.

OPTIONAL PARTS

INDOOR UNIT

**Connecting an connector cable to the air conditioner**

Models for which the mounting cord clamp is used



Models for which the fastener is used

