

LED DRIVER 12V 10W

astro

SPECIFICATION

TYPE:	Constant Voltage
DRIVER CURRENT (mA):	N/A
DRIVER VOLTAGE (V):	12
DIMMABLE:	Leading/Trailing Edge
ELECTRICAL CLASS:	Class 2
SUPPLY VOLTAGE (V):	220-240V AC
SUPPLY FREQUENCY (Hz):	50
POWER FACTOR:	0.9
MIN. OUTPUT VOLTAGE (V DC):	0
MAX. OUTPUT VOLTAGE (V DC):	12
MIN. OUTPUT CURRENT (A):	0
MAX. OUTPUT CURRENT(A):	0.83
INRUSH CURRENT(A):	1.7A 40µsec
IP RATING:	IP20
WORKING TEMPERATURE (°C):	-25 - +50
CONNECTION TYPE:	Screw Terminals
LENGTH (mm):	101.5
WIDTH (mm):	51
HEIGHT (mm):	29.5
MIN. CIRCULAR APERTURE (mm/inch):	59mm/2-5/16"
MAX. LED DISTANCE (m):	2
MANUFACTURER:	TRIDONIC
MODEL NUMBER:	LCBU 10W 12V BASIC phase-cut SR



CODE: 6008038

Wire LED products in parallel.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.