



LD-MRS400001

LD-MRS

3D LIDAR SENSORS





Ordering information

| Туре | Part no. |
|--------------|----------|
| LD-MRS400001 | 1045046 |

Other models and accessories → www.sick.com/LD-MRS



Detailed technical data

Features

| Application | Outdoor |
|----------------------------|---|
| Light source | Infrared light (905 nm, ± 10 nm) |
| Laser class | 1 (IEC 60825-1:2014, EN 60825-1:2014) |
| Aperture angle | |
| Horizontal | 85° (Working range with 4 scan layers, 25° extension of working range with 2 scan layers to a total of $110^\circ)$ |
| Vertical | 3.2° |
| Scanning frequency | 12.5 Hz 50 Hz |
| Angular resolution | 0.125° 0.25° 0.5° |
| Working range | 0.5 m 320 m |
| Scanning range | |
| At 10% remission factor | 50 m |
| Amount of evaluated echoes | 3 |

Mechanics/electronics

| Connection type | Circular plug-in connector |
|------------------------|----------------------------|
| Supply voltage | 9 V 30 V |
| Power consumption | 8 W |
| Housing | Al |
| Housing color | Gray (RAL 7032) |
| Enclosure rating | IP69K |
| Protection class | III |
| Weight | 1 kg |
| Dimensions (L x W x H) | 94 mm x 165 mm x 88 mm |
| МТВБ | > 100 years |

Safety-related parameters

| MTTF _D | > 100 years |
|-------------------|-------------|
| _ | |

Performance

| Detectable object shape | Almost any |
|-------------------------------|------------------------|
| Systematic error | ± 300 mm ¹⁾ |
| Statistical error | 100 mm ¹⁾ |
| Integrated application | Field evaluation |
| Number of field sets | 16 fields |
| Simultaneous evaluation cases | 16 |

 $^{^{1)}\ \}mbox{Typical value;}$ actual value depends on environmental conditions.

Interfaces

| Ethernet | √ , TCP/IP, RS-232 |
|------------------------|---|
| Function | Raw data interface/parameterization Auxiliary interface Auxiliary interface |
| Data transmission rate | 100 Mbit/s 57,600 Baud |

Ambient data

| Ambient operating temperature | -40 °C +70 °C |
|-------------------------------|---------------|
| Ambient light immunity | 100 klx |


General notes

| Note on use | The sensor does not constitute a safety component as defined by relevant legislation on machine safety. |
|-------------|---|
| | Chille Salety. |

Classifications

| ECLASS 5.0 | 27270990 |
|----------------|----------|
| ECLASS 5.1.4 | 27270990 |
| ECLASS 6.0 | 27270913 |
| ECLASS 6.2 | 27270913 |
| ECLASS 7.0 | 27270913 |
| ECLASS 8.0 | 27270913 |
| ECLASS 8.1 | 27270913 |
| ECLASS 9.0 | 27270913 |
| ECLASS 10.0 | 27270913 |
| ECLASS 11.0 | 27270913 |
| ECLASS 12.0 | 27270913 |
| ETIM 5.0 | EC002550 |
| ETIM 6.0 | EC002550 |
| ETIM 7.0 | EC002550 |
| ETIM 8.0 | EC002550 |
| UNSPSC 16.0901 | 41111615 |

Dimensional drawing (Dimensions in mm (inch))




- ① Venting element
- ② "Ethernet" connection, 4-pin female connector
- 3 Connection data interface / synchronisation, 12-pin female connector
- Connection "Power", 4-pin female connector
- ⑤ Sensor coordinate origin

Working range diagram

Working range diagram 50 m

Scanning range in m (ft)



Scanning range for objects up to 10 % remission 50 m (164.04 ft)

2 measuring layers

4 measuring layers

Recommended accessories

Other models and accessories → www.sick.com/LD-MRS

| | Brief description | Туре | Part no. | | |
|--------------|--|------------------------|----------|--|--|
| Terminal and | Ferminal and alignment brackets | | | | |
| 19 CM | Bracket for LD-MRS, alignment adjustable in 2 axes | Alignment bracket | 1047429 | | |
| Others | | | | | |
| 1 6. | Connection type head A: Male connector, round plug, 4-pin, straight Connection type head B: Male connector, RJ45, straight Signal type: Ethernet Cable: 8 m Description: Ethernet, shielded Note: Connects the Ethernet interface of the LD-MRS to the Ethernet interface of the PC | YM2Z14- 080EC3MRJA8 | 2049827 | | |
| 1 10 | Connection type head A: Female connector, round socket, 4-pin, straight Connection type head B: Flying leads Cable: 8 m Description: Shielded Connection systems: Flying leads | YM2Z14- 080VA4M2Z12 | 2049824 | | |

Recommended services

Additional services → www.sick.com/LD-MRS

| | Туре | Part no. |
|--|--|----------|
| Commissioning | | |
| Product area: 2D LiDAR sensors, 3D LiDAR sensors Range of services: Inspection of connection, fine adjustment, configuration of monitored areas, configuration and optimization of parameters as well as tests, Setup of previously defined functions of basic settings, parameters of field application, filters for raw data output and product-specific configuration Travel expenses: The prices do not include travel costs such as hotel, flight, travel time and expenses. Duration: Additional work will be invoiced separately | Commissioning LiDAR sensors | 1680672 |
| Maintenance | | |
| Product area: 2D LiDAR sensors, 3D LiDAR sensors Range of services: Inspection, analysis and restoring of defined functions, Inspection and adaptation of basic settings, parameters of field application, filters for raw data output, and product-specific configuration Duration: Additional work will be invoiced separately Travel expenses: The prices do not include travel costs such as hotel, flight, travel time and expenses. | Maintenance of LiDAR sensors | 1682593 |
| Extended warranty | | |
| Product area: Identification solutions, machine vision, Detection and ranging solutions, safety camera sensors, Safety laser scanners, Safety radar sensors Range of services: The services correspond to the scope of the statutory manufacturer warranty (SICK general terms of delivery). Duration: Five-year warranty from delivery date. | Extended warranty for a total of five years from delivery date | 1680671 |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

