

Data Sheet

# H-Piece Valves, Type RLV-K, for Valve Radiators in One- and Two-Pipe Systems

Application



*RLV-K straight,  
radiator connection G 1/2 and G 3/4 A*



*RLV-K angle,  
radiator connection G 1/2 and G 3/4 A*



By means of the H-piece valve type RLV-K, every valve radiator with a centre distance between the connections of 50 mm can be blocked individually, e.g. in order to carry out trouble-free maintenance without affecting other parts of the system.

H-piece valve type RLV-K is nickel plated and is available in straight and angle versions. Special adapters ensure that the H-piece valve can be used both for radiators with an internal thread of G 1/2 and with an external thread of G 3/4 A. All adapters are self-sealing.

RLV-K is factory set for two-pipe operation. By adjusting the bypass spindle RLV-K can easily be changed to one-pipe system operation.

By adjusting the bypass spindle the radiator share can be set to desired value.


A fill and drain tap is available as an accessory to RLV-K.

Connection to copper, soft steel, PEX and Alupex pipes is made with Danfoss compression fittings. See separate data sheet.


In order to avoid deposition and corrosion, the composition of the hot water should be in accordance with the VDI 2035 guideline (Verein Deutscher Ingenieure).

System

*Two-pipe system*



*One-pipe system*



Data and Ordering

| Type  | Version  | Connection |        | Max. operation pressure | Test pressure | Max. water temperature | Code no. |
|-------|----------|------------|--------|-------------------------|---------------|------------------------|----------|
|       |          | Radiator   | System |                         |               |                        |          |
| RLV-K | Angle    | G ½ A      | G ¾ A  | 10 bar                  | 16 bar        | 120 °C                 | 003L0282 |
|       | Straight |            |        |                         |               |                        | 003L0280 |
|       | Angle    | G ¾ A      | G ¾ A  |                         |               |                        | 003L0283 |
|       | Straight |            |        |                         |               |                        | 003L0281 |

Accessories

| Product                                                                                    | Code no. |
|--------------------------------------------------------------------------------------------|----------|
| Fill and drain tap without nickel plating, with ¾" external thread and hose nozzle         | 003L0152 |
| Adapter incl. seal for valve radiator with G ¾ A external thread, pack of 20 pcs.          | 003L0292 |
| Self-sealing connection piece for valve radiator with G ½ internal thread, pack of 20 pcs. | 003L0295 |


Capacity in Two-Pipe Systems

| Valve | $K_{v5}$ -value <sup>1)</sup> (m³/h) | $K_v$ -value <sup>2)</sup> (m³/h) |
|-------|--------------------------------------|-----------------------------------|
| RLV-K | 1.4                                  | 0.7                               |

Factory setting for RLV-K is two-pipe operation. This means the radiator share is 100%.

- <sup>1)</sup> The  $k_{v5}$ -value states the flow volume (Q) through the RLV-K on its own, with the RLV-K in factory setting.
- <sup>2)</sup> The  $k_v$ -value is the flow volume (Q) through the RLV-K valve in combination with a Danfoss RTD-N built-in valve with  $k_v = 0.78 \text{ m}^3/\text{h}$  at  $X_p = 2 \text{ K}$ .

Capacity and Bypass Setting in One-Pipe Systems



From the factory RLV-K is set for two-pipe operation, which means the bypass is closed.


*Example:*  
Bypass setting for correct radiator share

Changeover to one-pipe operation is done by opening the bypass spindle. See below.

*Given:*  
 $K_v$ -value for radiator with thermostatic valve:  
0.4 (m<sup>3</sup>/h)  
Desired radiator share: 30%

Desired flow and radiator share is set using the bypass spindle.

*Solution:*  
Right graph shows that bypass spindle must be turned 2 turns. Left graph shows the total  $k_v$  of radiator with built-in valve and RLV-K valve.




**Draining of the Radiator**


To drain the radiator, first unscrew the cover caps. Then shut-off inlet and return.

When the drain tap has been mounted, open valve outlet by turning the Allen screw as shown.

The hose nozzle can rotate freely in any direction.



Design




**Materials in contact with water**


|                                  |       |
|----------------------------------|-------|
| Valve body and other metal parts | Ms 58 |
| O-ring                           | EPDM  |

Dimensions


*RLV-K straight, G 1/2 radiator connections*




*RLV-K angle, G 1/2 radiator connections*



*RLV-K straight, G 3/4 radiator connections*



*RLV-K angle, G 3/4 radiator connections*









Danfoss A/S  
Heating Solutions  
Haarupvaenget 11  
8600 Silkeborg  
Denmark  
Phone: +45 7488 8000  
Fax: +45 7488 8100  
Email: [heating.solutions@danfoss.com](mailto:heating.solutions@danfoss.com)  
[www.heating.danfoss.com](http://www.heating.danfoss.com)

---

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---