



Connecto

The Danfoss Connecto programme gives you different solutions for easy and safe connection of Danfoss self-limiting heating cables - ECiceguard, SLPG, EChotwatt.

Using Danfoss Connecto to wire up a heating circuit is fast, requiring only a knife and a diagonal cutter.

Product specifications





Benefits • Fast and easy to install • Cost savings by reduced assembly time • Great reliability of assembly simplicity • Safe electrical contacting by precise clamp cutting technology Compliance symbols:   	Nominal voltage, max.	250 V~
	Max. current	16 A
	Ambient temperature	-25 °C to +60 °C
	On request	-25 °C to +85 °C
	IP class	IP 66

Types

Item no.	Product name	Description	EAN no.
088L0413	Connecto B-A	Connection power supply	5703466130247
088L0414	Connecto B-C	Heating cable connection	5703466130254
088L0415	Connecto B-E	End termination	5703466130261
088L0416	Connecto B-S	Connection termination	5703466130278
088L0417	Connecto B-T	Y-junction + end termination	5703466130285
088L0418	Connecto B-TE2	Y-junction + 2 end terminations	5703466130292
088L0419	Connecto B-TE3	Y-junction + 3 end terminations	5703466130308
088L0420	Connecto B-X	X-junction + 2 end terminations	5703466130315

ATTENTION. Danfoss Connecto may not be put in the gutters when used with ECiceguard. Must be installed in a dry place.

Selection chart. Danfoss Connecto for heating cables with braiding: SLPG, EChottwatt (B)

Illustration	Name	Description
	Connecto B-S	Heating cable connection with 1,5 m power cable and 1 end terminal
	Connecto B-C	Heating cable slice/extension for connecting two heating cables
	Connecto B-T	Heating cable T-branch as a T-junction for three heating cables and 1 end terminal
	Connecto B-TE2	Heating cable double connection with 1,5 m power cable and 2 end terminals
	Connecto B-TE3	Heating cable T-branch with 1,5 m power cable and 3 end terminals
	Connecto B-X	Heating cable X-branch for 4 heating cables incl. 2 end terminals
	Connecto B-A	Heating cable connection with power cable 1,5 m without end terminal
	Connecto B-E	Heating cable end terminal
	Connecto Bracket	For installation of the Danfoss Connecto connection outside the insulation

Connecto system installation steps

1. Cut the heating cable straight
2. Push the heating cable in
3. Twist until closed



Connecto B-C



Connecto B-TE2



Connecto B-X