



DEVI ACCESSORIES

Data sheet

Fastening for down pipes

Picture	Name	Description/Technical data		Art. no.	
	Cable fixing for down - pipe suspension	Dimensions Chain hole size 1 bag with 25 pcs.	- 37 x 20 x 6 mm - 8 mm	Art. no. 19805258 EAN no. 5703466003763	
	Relief clip single for drain pipes	Dimensions Minimum order quantity	- 35 x 10 x 10 mm - 10 pcs.	Art. no. 19406007 EAN no. 5703466154229	
	Relief clip for drain pipes	Dimensions Minimum order quantity	- 50 x 10 x 10 mm - 10 pcs.	Art. no. 19406008 EAN no. 5703435003015	
	DEVIfast™ Double Special RB 25m	Metal fixing tape for resistive heating cable. Cable types Width Length Fixing distance Cable C-C distance Material	- Resistive - 50 mm - 5 mm - 10 cm (on one side) - 30-35 mm - Galvanized steel	Art. no. 19808185 EAN no. 5703466240397	
	DEVIfast™ Double for SLC RB 25m	Metal fixing tape for self-limiting heating cables. Cable types Width Length Fixing distance Cable C-C distance Material	- SLC and resistive - 65 mm - 25 mm - 15 cm (on one side) - 40-45 mm (SLC) - Galvanized steel	Art. no. 19808183 EAN no. 5703466240380	
	Entlastungsseil	500 x 15 x 1 mm Cut-to-length		Art. no. 19406016 EAN no. 5703435003022	
	Longlinked chain 4 mm c4 x 32 din 5685 fzn	Chain hole size Cut-to-length	- 8 mm - 1...25 m	Art. no. 19805241 EAN no. 5703435003060	
	Traverse v 2 a	Dimensions	- 288 x 25 x 5 mm	Art. no. 19805449 EAN no. 5703435003077	

Fastening for roof and gutters

Picture	Name	Description/Technical data	Art. no.	EAN no.
	DEVIfast™ Double Special RB 25m	Metal fixing tape for resistive heating cable. Cable types - Resistive Width - 50 mm Length - 5 mm Fixing distance - 10 cm (on one side) Cable C-C distance - 30-35 mm Material - Galvanized steel	19808185	5703466240397
	DEVIfast™ Double for SLC RB 25m	Metal fixing tape for self-limiting heating cables. Cable types - SLC and resistive Width - 65 mm Length - 25 mm Fixing distance - 15 cm (on one side) Cable C-C distance - 40-45 mm (SLC) Material - Galvanized steel	19808183	5703466240380
	DEVIfast™ Copper 25 m In box	Copper type is used for fastening heating cables and ensure the correct C-C distance. Width - 21 mm. Material - Copper. Cable C-C fixing - in each 25 mm	19808238	5703466214695
	DEVIfast™ roofhook, installation kit	Roofhook - 25 pcs. Cable Strip 7,6x203 mm, black - 25 pcs.	19805192	5703466134757
	DEVIfast™ guardhook Install. kit	Base Roof accessories - 20 pcs. Angle Roof accessories - 10 pcs. Cable Strip 7,6x203 mm, black - 30 pcs.	19805193	5703466145470
	Roof Gutter Clip with hinge	1 bag with 25 pcs.	140F1511	5703466229897

Fastening for floors

Picture	Name	Description/Technical data	Art. no.	EAN no.
	DEVIclip™ c-c	500 x 50 x 60 mm, 20 pcs. in bag.	19805220	5703466173213
	DEVIclip™ Twisto	Plastic Bag with 1000 pcs.	19805236	5703466172117
	DEVIfast™ Metal 5 m In box	Metal type is used for fastening heating cables and ensure the correct C-C distance. Width - 21 mm. Material - Metal covered by galvanized zinc Cable C-C fixing - in each 25 mm	19808234	5703466214671
	DEVIfast™ Metal 25 m In box		19808236	5703466214688
	Montagestege type ms 5,6-6,5 mm - 25mm	980 x 10 x 10 mm 1 pc.	109030	5703466134740
	Montagestege type ms 6,6-8,0 mm - 25mm	1000 x 10 x 10 mm 1 pc.	19805266	5703435009222
	Synthetic nail	Box with 40 pcs.	19805907	5703466249536

DEVicell™ accessories

Picture	Name	Description/Technical data	Art. no.	EAN no.
	Flexkit for DEVicell™	Package 170 x 250 x 20 mm	18055300	5703466128893
	EPS-Randplatten W25 DEVicell™ L100	Edge plates for DEVicell™ Size 1000x250x15 mm Plastic type EPS Max working temp. 85 °C Deformation strength >120 kPa at 10% compression 1 pc.	00109200	5703466194560
	Connective clips for DEVicell™	Connective plastic clips for mounting plate Devicell Dry, 5x10 pcs.	15992250	5703466129340

Cold leads

Picture	Name	Description/Technical data	Art. no.	EAN no.
	DTWK Cold lead 2x2.5mm ² w/screen	Cold lead for DEVlasphalt™, cut-to-length	Art. no. 140F0902	EAN no. 5703466233344
	DSWA Cold lead 1x1.5mm ² w/screen	Cold lead for DEVlbasic™, cut-to-length	Art. no. 140F0903	EAN no. 5703466233351
	DSWA Cold lead 1x2.5mm ² w/screen	Cold lead for DEVlbasic™, DEVIsport™, cut-to-length	Art. no. 140F0904	EAN no. 5703466233368
	DSWA Cold lead 1x4.0mm ² w/screen	Cold lead for DEVlbasic™, DEVIsport™, cut-to-length	Art. no. 140F0905	EAN no. 5703466233375
	DTWB Cold lead 2x1.0mm ² w/screen	Cold lead for DEVlmat™, DEVlcomfort™, cut-to-length	Art. no. 140F0906	EAN no. 5703466233382
	DTCL Cold lead 3x1.5mm ²	Cold lead for DEVIflex™, DEVIsafe™, DEVIsnow™, cut-to-length	Art. no. 140F0907	EAN no. 5703466233399
	DTCL Cold lead 3x2.5mm ²	Cold lead for DEVIflex™, DEVIsafe™, DEVIsnow™, cut-to-length	Art. no. 140F0908	EAN no. 5703466233405

Tapes / Glue / Tools

Picture	Name	Description/Technical data	Art. no.	EAN no.
	Acrylic coated cloth tape 15 mm x 50 m (Textilklebeband)	Strong acrylic coated cloth tape for almost every application with high adhesion even on rough surfaces, e.g. for fixing cable to concrete or on pipe, insulating of wires, etc. Color gray Backing material acrylic-coated cloth Total thickness 310 µm Type of adhesive natural rubber Adhesion to steel 3.3 N/cm Elongation at break 13 % Tensile strength 100 N/cm Temperature resistance 130 °C (30 min) Mesh 145 count per inch ² Producer type tesa® 4651	Art. no. 19405877	EAN no. 5703435002971
	Tape aluminium 38 mm x 50 m	Self-adhesive, with 2-colour warning text, max. 160 °C Backing Aluminium foil Adhesive Waterbased Acrylic Liner Monosiliconized Paper Adhesion/Steel 8 N/ 38 mm Tensile strength 57,5 N/ 38 mm Total thickness 60 µm	Art. no. 19805076	EAN no. 5703435003053
	Tape aluminium 25 mm x 25 m	Self-adhesive, with 2-colour warning text, max. 160 °C. Backing Aluminium foil Adhesive Waterbased Acrylic Liner Monosiliconized Paper Adhesion/Steel 8 N/ 25 mm Tensile strength 57,5 N/ 25 mm Total thickness 60 µm	Art. no. 19805078	EAN no. 5703466130469
	Hotmelt gluesticks	170 x 250 x 20 mm 1 bag with 25 pcs.	Art. no. 18055351	EAN no. 5703466114940
	DEVI turntable™	Ø400 x 70 mm 1 pc.	Art. no. 19805250	EAN no. 5703466173220


Connection/repair sets

Picture	Name	Description/Technical data	Art. no.	EAN no.
	DEVIcrimp™ repair set 1-cond. mat	Connection/repair set for 1-conductor DEVIheat™, DEVIheat™ Sport 90S, 2 connections in the set. Package 170 x 230 x 20 mm	Art. no. 18055240 EAN no. 5703435037980	
	DEVIcrimp™ repair set 2-cond mat	Connection/repair set for 2-conductor DEVIcomfort™ and DEVImat™, 2 connections in the set. Package 170 x 230 x 20 mm	Art. no. 18055510 EAN no. 5703466074091	
	DEVIcrimp™ kit 1-cond. Assembly or repair gb/fi	Connection/repair set for 1-conductor DEVIbasic™, DEVIsport™, 2 connections in the set. Shrink tube 12/3 Black 20 cm - 2 pc. CU-socket 14 cm - 2 pcs. Shrink tube 6/1,4 Black 4 cm - 2 pcs. Double tubular rivet 1,5-2,5 mm² - 2 pcs. Wire CU BLW 0,248 R/m 0,30 mm - 1 m	Art. no. 18055442 EAN no. 5703466003435	
	DEVIcrimp™ CS-2C assembly kit dk 2-cond.	End termination repair set for 2-conductor cable DEVIflex™, DEVI-safe™, DEVIsnow™. Shrink tube 12/3 Black 10 cm - 1 pc. Shrink tube 6/1,4 Thin Black 4 cm - 1 pc. CU-socket 6 cm - 1 pc. Tubular rivet 0,5-1,0 mm² - 1 pc. Wire CU BLW 0,248 R/m 0,30mm - 1 m Package 170 x 230 x 20 mm	Art. no. 18055230 EAN no. 5703466068991	
	Connection/Repair kit for Flex, Safe, Snow cables	Connection/Repair kit with end termination for DEVIflex™, DEVI-safe™, DEVIsnow™ cables in the set. Parallel splice Non-insulated 1,04-2,63 mm² - 6 pcs. Parallel splice Non-insulated 0,25-1,65mm² - 1 pcs. Shrinktube 12/3 IAKT, 85 mm - 3 pcs. Shrinktube 6/1,4 clear w. Glue 40 mm - 7 pcs. Shrinktube 19/5 IAKT, 135 mm - 2 pcs. DTCL 3G 1,5mm² black PVC, 0,3 m - 1 pcs.	Art. no. 18055350 EAN no. 5703466003381	
	DEVIcrimp™ ass/repair kit 2-cond. for DEVIasphalt™ (DTIK)	Connection/repair set with spacer for 2-conductor DEVIasphalt™, 2 connections in the set. Shrink tube 20/6 HTC-SCM-HD Black 160 mm - 2 pcs. DTWK 25 cold tail - 0,3 m Shrink tube 18/4,5 Clear 70 mm - 2 pcs. Spacer PPS - 2 pcs. Double tubular rivet 1,5-2,5 mm² - 6 pcs.	Art. no. 18055355 EAN no. 5703466195192	
	DEVIcrimp™ assembly set dk 4-cond. Type CS-4A	Assembly set for 4-conductor DEVImulti - set for 1 connection or 1 cold tail or 1 end muff. Shrink tube 19/5 Black 25 cm - 1 pc. Shrink tube 12/3 Black 15 cm - 1 pc. CU-stocking 25 cm - 1 pc. Double tubular rivet 1,5-2,5 mm² - 5 pcs. Shrink tube 6/1,4 Black 5 cm - 4 pcs. Wire CU 0,30 mm - 1 m	Art. no. 19805480 EAN no. 5703466003824	
	DEVIcrimp™ assembly set dk 4-cond. Type CS-4B DEVIcrimp™ terminal set dk 4-cond. Type CS-4/1	Assembly set for 4-conductor DEVImulti - set for 2 connections 1 cold tail and 1 end muff or 2 cold tails or 2 end muffs. Shrink tube 19/5 Black 25 cm - 2 pcs. Shrink tube 12/3 Black 15 cm - 2 pcs. CU-stocking 25 cm - 2 pcs. Double tubular rivet 1,5-2,5mm² - 10 pcs. Shrink tube 6/1,4 Black 5 cm - 8 pcs. Wire CU 0,30 mm - 1 m	Art. no. 19805712 EAN no. 5703466003855	
	Repair kit with compound for heating cables Concrete/støbesæt gb/dk	Connection/repair set with compound for DEVIflex™, DEVI-safe™, DEVIsnow™, DEVIbasic™, DEVImulti™. Package 130 x 265 x 75 mm	Art. no. 19805704 EAN no. 5703466003848	

Crimp sets for DEVpipeguard™ 30/60 Industry


Picture	Name	Description/Technical data	Art. no.	EAN no.
	Connection kit for DEVpipeguard™ 30/60 Industry (PT-30/60) heating cables	With clamping block for the connection of cold lead and heating cable, shrink end-cap, shrink tubes, bitumen gaskets and ferrules. Shrinktube 33/5,5 Black no glue, 17 cm - 1 pc. Clamping block 5x2,5 mm ² - 1 pc. Shrink end-cap 20/8, 75 mm - 1 pc. Shrinktube 12/3 Black, 2,5 cm - 1 pc. Shrinktube 16/3 yellow-green, 2,5 cm - 1 pc. Bitumen gasket 1,5x85x35 mm - 3 pcs. Wire end ferrule 1,5 mm ² - 2 pcs. Wire end ferrule 2,5 mm ² - 1 pc.	00109007	5703466167397
	Connection kit for DEVpipeguard™ 30/60 Industry (PT-30/60) heating cables	For mounting in connection box with crew connections. With cable gland M20x1,5 with locknut, shrink end-cap, shrink tubes, bitumen gasket and ferrules. Shrink end-cap 20/8, 75 mm - 1 pc. Bitumen gasket 1,5x85x35 mm - 1 pc. Cable gland U17 M20x1,5 - 1 pc. Shrinktube 12/3 Black, 2 cm - 2 pcs. Shrinktube 4/1 Black, 8 cm - 2 pcs. Shrinktube 16/3 yellow-green, 8 cm - 1 pc. Wire end ferrule 1,5 mm ² , 7 mm - 2 pcs. Wire end ferrule 2,5 mm ² , 8 mm - 1 pc.	00109026	5703466135778

Crimp sets for DEVpipeheat™ 10


Picture	Name	Description/Technical data	Art. no.	EAN no.
	Connection kit - cable to junction box + end termination (Pipeheat)	Connection set with end-cap for connection DEVpipeheat™ 10 V2 and V3 to junction box or connection housing and assembly end-termination. 4/1 Heat shrink tube, 100 m - 2 pcs. 9/3 Heat shrink tube, 20 mm - 1 pcs. ø2 mm Tube Yellow/Green, 100 mm - 1 pcs. 6/1,4 Heat shrink tube, 20 mm - 1 pcs. 12/3 Heat shrink tube, 85 mm - 1 pcs.	140F0954	5703466071830
	Connection kit - cable to cold lead + end termination (Pipeheat)	Connection set with end-cup for assembly between DEVpipeheat™ 10 V2 and V3 and cold lead/SLC and assembly end-termination. 19/5 Heat shrink tube, 150 mm - 1 pcs. 9/3 Heat shrink tube, 85 mm - 1 pcs. 4/1 Heat shrink tube, 45 mm - 3 pcs. Double tubular rivet, 0,5-1,0 mm ² - 3 pcs. 6/1,4 Heat shrink tube, 20 mm - 1 pcs. 12/3 heat shrink tube, 85 mm - 1 pcs.	140F0955	5703466074985
	3/4\"+1\" Pipe Fitting DEVpipeheat™ 10 V3	Wadding for Internal mounting In pipe for DEVpipeheat™ 10 V3 Stainless steel pipe fitting and nut. Rubber conic sliced sleeve, oval hole. Max. water pressure - 10 bar at max. water temperature 23 °C	140F0956	5703466250037

Crimp sets for DEVpipeguard™, DEVliceeguard™, DEVIhotwatt™

Picture	Name	Description/Technical data	Art. no.	EAN no.
	Con. Kit, cable/box self-limiting cables, dk/gb	Connection set with end-cap and flathole packing for connection DEVpipeguard™, DEVliceeguard™ or DEVIhotwatt™ to junction box or connection housing and assembly end-termination. Shrinkfit End-cap 14/4,5 60 mm - 1 pc. Hot melt tape 0,5x25 mm 6,7 cm - 1 pc. Hot melt tape 0,5x25 mm 10 cm - 1 pc. Shrink tube 19/9,5 Clear 10 cm - 1 pc. Shrink tube 12/3 Black 2,5 cm - 1 pc. Wire CU 0,30 mm - 1 m Shrink tube 12/3 Black 2 cm - 1 pc. Flathole packing PG16 ø20 mm SLC - 1 pc. Shrink tube 4/1 Black 7 cm - 2 pcs. Package 170 x 230 x 20 mm	19805753	5703466003879
	Con. Kit, cable/cold tail self-limiting cables, dk/gb	Connection set with end-cap for assembly between DEVpipeguard™, DEVliceeguard™ or DEVIhotwatt™ and cold lead/SLC and assembly end-termination. Hot melt tape 0,5x25 mm 10 cm - 1 pc. Shrink tube 19/9,5 Clear 10 cm - 1 pc. Shrinkfit End-cap 14/4,5 60 mm - 1 pc. Shrink tube 19/5 Black 135 mm - 1 pc. Double tubular rivet insul. 1,5-2,5 mm² - 3 pcs. Wire CU 0,30 mm - 1 m Shrink tube 12/3 Black 2,5 cm - 1 pc. Shrink tube 12/3 Black 2 cm - 1 pc. Shrink tube 4/1 Black 1,5 cm - 2 pcs. Package 170 x 230 x 20 mm	19805761	5703466003886
	Con. Kit, cable/cable self-limiting cables, dk/gb	Fitting set for joining of self-limiting cables DEVpipeguard™, DEVliceeguard™, DEVIhotwatt™ to self-limiting cable. Shrink tube 12/3 Black 4 cm - 1 pc. Shrink tube 19/5 Black 4 cm - 1 pc. Shrink tube 12/3 Black 8 cm - 1 pc. Hot melt tape 0,5x25 mm 10 cm - 1 pc. Shrink tube 19/9,5 Clear 17 cm - 1 pc. Shrink tube 3/1 Black 6 cm - 1 pc. Soldering tin 0.8 mm RA - 1 m Double tubular rivet insul. 1,5-2,5 mm² - 3 pcs. Tape TESA Black 15mm roll 10 m - 1 pc. Package 170 x 230 x 20 mm	19805779	5703466003893
	DEVicrimp™ t-connection for self-limiting cables	Fitting set for joining of 1 self-limiting cable DEVpipeguard™, DEVliceeguard™ or DEVIhotwatt™ to 2 self-limiting cables with T-connection. Shrink tube 19/5 Black 25 cm - 1 pc. Shrink tube 19/5 Black 18 cm - 1 pc. Shrink tube 19/9,5 Clear 10 cm - 1 pc. Shrinkfit End-cap 14/4,5 60 mm - 1 pc. Hot melt tape 0,5x25 mm 10 cm - 1 pc. Shrink tube 9/3 Black 2 cm - 4 pc. Shrink tube 9/3 Black 3,5 cm - 2 pc. Double tubular rivet 4 mm² - 1 pc. Double tubular rivet 1,5-2,5 mm² - 2 pcs. Shrink tube 4/1 Black 4 cm - 6 pc. Hot melt tape 0,5x25 mm 6 cm - 7 pc. Shrink tube 18/4,5 Splicemelt 12 cm - 1 pc. Package 230 x 320 x 20 mm	19806421	5703466169780

Picture	Name	Description/Technical data	Art. no.	EAN no.
	ANSCHLGAR. M/KLEM Z.VERB.VON FLEXIB. KALT (Anschlussgarnitur, mit Klemmstein zur Verbind- ung von flexibler Kalt- leitung und Heizband, Endabschluss)	Connection set with clamping block and with end-termination for assembly between DEVpipeheat™, DEVhotwatt™, DEViceguard™ and cold lead. Shrinktube 24/8 Black 12 cm - 1 pc. Clamping block 5x2,5 mm ² - 1 pc. Shrinkfit end-cap TEC12-4 - 1 pc. Shrinktube 12/3 Black, 2,5 cm - 1 pc. Shrinktube 3/1,6 yellow-green, 2,5 cm - 1 pc. Wire end ferrule 1,5 mm ² - 2 pcs.	19400126	5703435002810
	Endcap	Shrinkfit End-cap TEC12-4 Package 245 x 10 x 170 mm 1 pc. in a bag	19400142	5703435002834
	Anschlussgarnitur fuer poestergehaeuse	Connection set with end-cap for connection self-limiting cables to junction box or connection housing and assembly end-termination. Shrinkfit End-cap TEC12-4 - 1 pc. Cable gland M20, Hole: 5x7,5 mm oval - 1 pc. Cable gland M25, Hole: 5x11,5 mm oval - 1 pc. Shrink tube 12/3 Black 2 cm - 2 pcs. Shrink tube 3/16 Yellow/Green 8 cm - 1 pc. Shrink tube 4/1 Black 8 cm - 2 pcs. Wire end ferrule 1,5 mm ² - 2 pcs. Package 250 x 25 x 165 mm	19400100	5703435002797
	Insulation introduction	Cable gland M20, Hole: 5x7,5 mm oval - 1 pc. Cable gland M25, Hole: 5x11,5 mm oval - 1 pc. Metal mounting plate M20 60x60x1 mm AISI304 - 1 pc.	11010410	5703435031001
	Flathole packing PG16 for self-limiting cables	For cable gland M25 for self-limiting cables DEViceguard™, DEVpipeguard™ and DEVhotwatt™. Size: ø20x6 mm. Hole size: 5x11,5 mm, oval. Minimum order quantity 20 pcs.	19805787	5703435009192


Junction box and accessories


Picture	Name	Description/Technical data	Art. no.	EAN no.
	Junction box 0,75-2,5 mm² 7xM20	Box for indoor installation. Rated insulation voltage $U_i = 690$ V AC/DC Rated current 20 A Material PP (polypropylene) Degree of protection IP 66 Width 93 mm Height 93 mm Depth 62 mm Weight 0,129 kg Tightening torque 0,5 Nm In accordance with IEC 60670-22	19400167	5703435002858
	Junction box 1,5-4 mm² 7xM20/ M25 UV	Weatherproof box for outdoor installation. Terminal 2 clamping units/pole, 5-pole, per pole 8x1,5 mm ² r/f, 6x2,5 mm ² r/f, 4x4 mm ² r/f, 2x6 mm ² r/f Rated insulation voltage $U_i = 690$ V AC/DC Rated current 32 A Material PC-GFS (polycarbonate) Degree of protection IP 66 / IP 67 / IP 69; IP 67, temporary submersion; IP 69, water pressure max. 100 bar, water temp. max. 80°C, distance $\geq 0,15$ m Size 104x104x70 mm weight 0,17 kg tightening torque 0,7 Nm in accordance with IEC 60670-22 in accordance with DNV GL - Certificate No TAE00000EE Russian Maritime Register of Shipping, approved by the letter No. 250-A-1180-108795 No. 250-A-1180-108795	19400165	5703466248539
	Bracket	Fitting for connection of housing or junction box to pipes, etc. 1 pc.	19405851	5703435002964

Fastening

Picture	Name	Description/Technical data	Art. no.	EAN no.
	Heizbandhalter v2a 10 cm cc 10 cm	1000 mm x 30 mm 1 pc.	19805300	5703466075104
	Heizbandhalter v2a 15 cm cc 15 cm	1000 mm x 30 mm 1 pc.	19805301	5703466195789
	Spaceclip for self-limiting cables	300 x 5 x 70 mm, stainless steel AISI 304 1 pc.	19805746	5703435010501
	Cable ties	Package 300 x 120 x 20 mm 1 bag with 100 pcs.	00109004	5703466090282

DEVconnecto for DEVliceguard™ (B), DEVpipeguard™ (B), DEVhotwatt™ (B)

Picture	Name	Description/Technical data	Art. no.	EAN no.
	DEVconnecto B-A Connection	Package 130 x 265 x 75 mm	19808360	5703466103067
	DEVconnecto B-C Heating cable connection	130 x 265 x 75 mm	19808361	5703466103074
	DEVconnecto B-E End termination	130 x 265 x 75 mm	19808362	5703466103081
	DEVconnecto B-S Connection termination	130 x 265 x 75 mm	19808363	5703466103098
	DEVconnecto B-T, T-Junction + End termination	130 x 265 x 75 mm	19808364	5703466103104
	DEVconnecto B-TE2 Junction + 2 End termination	130 x 265 x 75 mm	19808365	5703466103111
	DEVconnecto B-TE3 Junction + 3 End termination	130 x 265 x 75 mm	19808366	5703466103128
	DEVconnecto B-X, X-Junction + 2 End termination	130 x 265 x 75 mm	19808367	5703466103135
	DEVconnecto Bracket, ref AH 61400005	Bracket for installation outside the insulation. Length 194 mm, high 55 mm, width 30 mm.	19808390	5703466125021



DEVI EasyConnect for DEVliceguard™ (T), DEVlpipeguard™ (T)

Picture	Name	Description/Technical data	
	DEVI EasyConnect EC-1 Power connection	Power supply connection set	Art. no. 98300870 EAN no. 5703466214503
	DEVI EasyConnect EC-T1 Heating cable connection	Connection set for 2 heating cables	Art. no. 98300871 EAN no. 5703466214510
	DEVI EasyConnect EC-ETK End termination	End plug set	Art. no. 98300872 EAN no. 5703466214527
	DEVI EasyConnect EC-1 +ETK Power con. + end term.	Power supply connection set with an end plug	Art. no. 98300873 EAN no. 5703466214534
	DEVI EasyConnect EC-T2 Heating cable con x 2	Set for heating cable branching – 1 to 2	Art. no. 98300874 EAN no. 5703466214541
	DEVI EasyConnect EC-2 Power connection x 2	Power supply connection set for 2 cables	Art. no. 98300875 EAN no. 5703466214558
	DEVI EasyConnect EC-3 Power connection x 3	Power supply connection set for 3 cables	Art. no. 98300876 EAN no. 5703466214565

DEVifoil™

Picture	Name	Description/Technical data	
	Cold lead 1 x 1.5 mm² Black 50 m	Flexible 1-core cable. U0/U = 450/750 V~. Max. 90/105 °C. Package 210 x 210 x 65 mm	Art. no. 00106010 EAN no. 5703466124086
	Cold lead 1 x 1.5 mm² Blue 50 m	Flexible 1-core cable. U0/U = 450/750 V~. Max. 90/105 °C. Package 210 x 210 x 65 mm	Art. no. 00106011 EAN no. 5703466124093
	Cold lead 1 x 2.5 mm² Black 50 m	Flexible 1-core cable. U0/U = 450/750 V~. Max. 90/105 °C. Package 210 x 210 x 65 mm	Art. no. 00106012 EAN no. 5703466124109
	Cold lead 1 x 2.5 mm² Blue 50 m	Flexible 1-core cable. U0/U = 450/750 V~. Max. 90/105 °C. Package 210 x 210 x 65 mm	Art. no. 00106013 EAN no. 5703466124116
	Duct tape 50 mm x 50 m (Lærredstape)	Strong self adhesive tape with typical duct features for a wide range of applications. It consists of a 27 mesh woven PET/cotton fabric backing coated with a natural rubber adhesive. Backing PE laminated cloth Total thickness 230 µm Type of adhesive natural rubber Adhesion to steel 4.4 N/cm Elongation at break 18 % Tensile strength 30 N/cm Temperature resistance 95 °C (30 min) Mesh 27 count per inch² Producer type tesa® 4662	Art. no. 98931300 EAN no. 5703466147894
	Tape 2-sided 25 mm x 50 m, double-faced	Double-sided tape with a non-woven backing. General purpose. The thick layer of adhesive bonds well on uneven surfaces and has a very high initial bond. Backing material non-woven Total thickness 110 µm Type of adhesive synthetic rubber Adhesion initial /> 14 days Steel 12/13 N/cm, PE 5,5/7 N/cm, PP 7/12 N/cm, PVC 9/12,5 N/cm Temp. resistance short term 80 °C, long term 40 °C Producer type tesa® 51570	Art. no. 98931301 EAN no. 5703466147900
	Vulkatape vm 38 mm x 6 m	For isolation of DEVifoil™ connectors after connecting to the foils powerlines	Art. no. 98931302 EAN no. 5703466147917
	Depron glue, 5 kg	Package 195 x 195 x 140 mm	Art. no. 00106017 EAN no. 5703466207338

Picture	Name	Description/Technical data	
	Connector for DEVifoil™ Floor, 500 pc (1 box)	Package 170 x 150 x 140 mm	Art. no. 98931203 EAN no. 5703466128893
	Pliers for connectors	Package 150 x 20 x 120 mm	Art. no. 98931205 EAN no. 5703466128923
	Depron®, 3 mm, 40 pc (1 box), -60 °C to +70 °C, 80 cm x 125 cm	1260 x 820 x 135 mm	Art. no. 00106014 EAN no. 5703466125137
	Depron®, 6 mm, 20 pc (1 box), -60 °C to +70 °C, 80 cm x 125 cm	1260 x 820 x 135 mm	Art. no. 00106015 EAN no. 5703466125144

For DEVireg™ 233

Picture	Name	Description/Technical data	
	DEVireg™ 233 Front, knob 1 pcs. in box, White		Art. no. 19805922 EAN no. 5703466164587
	DEVireg™ 233 Front, knob 1 pcs. in box, Light grey		Art. no. 19805923 EAN no. 5703466164594
	DEVireg™ 233 Front, knob 1 pcs.in box, Charcoal grey		Art. no. 19805924 EAN no. 5703466164600

For thermostats with flush-mounted fixing

Picture	Name	Description/Technical data	Art. no.	EAN no.
	Multiboks PFXP/red E-1223740	Package 76 x 71 x 55 mm	19808930	5703435003398
	Wall mounting Box EURO size w. ELKO Frame RS-16 L571 PH Bright rounded corners	Package 87 x 87 x 40 mm	19808932	5703466078242
	Wall box EURO size ELKO Plus 40mm E-1470812 sharp corners	Package 86 x 86 x 40 mm Single surface house ELKO Plus Colour Polarwhite Height 40 mm Halogenfree Screw distance, C-C 60 mm	189B9139	5703466213780

For DEVIreg™ 610


Picture	Name	Description/Technical data	Art. no.	EAN no.
	Pipe assembly set, dk	Package 85 x 85 x 32 mm	19116920	5703465002873

Sensors and accessories for sensors


Picture	Name	Description/Technical data	Art. no.	EAN no.
	Room sensor FUGA-frame, DK only	63 x 63 x 25 mm, NTC 15 kOhm at 25 °C, IP 20	140F1090	5703466209295
	Room sensor, 426-frame	85 x 85 x 30 mm, NTC 15 kOhm at 25 °C, IP 20	140F1095	5703466209684
	Outdoor sensor IP44	80 x 50 x 35 mm, NTC 15 kOhm at 25 °C, IP 44	140F1096	5703466209691

Picture	Name	Description/Technical data										
	Sensor cable 3 m, 15 kOhm, Santoprene	Wire sensor 2x0,75 mm ² , NTC 15 kOhm at 25 °C, Ø5 mm, black Santoprene (TPV) outer sheath, IP 67, Temp. range -25 °C to 90 °C	Temp., °C	Resistanse, kOhm	Art. no.	140F1091						
	Temperature Sensor 10 m NTC 15k Santoprene		-10	66,1	EAN no.	5703466209301						
			-5	52,5	Art. no.	140F1098						
			0	41,1								
			5	33,2								
			10	27,0								
			15	22,1								
			20	18,2								
	Temperature Sensor 40 m NTC15k Santoprene		25	15,0			EAN no.	5703466210734				
			30	12,3								
			35	10,4								
			40	8,7								
			45	7,4								
			50	6,2								
	Outdoor sensor 2,5 m, 15 kOhm, PVC, DIN 44574	Wire sensor, 2x0,75 mm ² , NTC 15 kOhm at 25 °C, Ø10 mm, white PVC outer sheath, IP 67, Temp. range -25 °C to 70 °C			Art. no.	140F1092						
					EAN no.	5703466209318						
		Silicon temperature sensor for DEVlreg™ 330 (60-160°C), NTC 16,1 kOhm @ 100°C	Wire sensor, 2,5 m, 2x0,75 mm ² , NTC 16,1 kOhm at 100 °C, Ø9 mm, IP 65, Temp. range 50 °C to 170 °C			Art. no.	140F1097					
						EAN no.	5703466209707					
			Flexpipe Ø6,7 mm, 2,5 m	Package 170 x 240 x 20 mm, inner Ø6,7 mm, outer Ø10 mm, Black			Art. no.	140F1114				
							EAN no.	5703466215234				
				AstroFlex FFYL Ø8,5 mm, roll 50 m	Package 400 x 130 x 400 mm, Flexpipe for sensor and cable protection.			Art. no.	19809100			
								EAN no.	5703435009314			
					Sensor shell M20	Size 95 x Ø20 mm inner Ø10,5 mm, inner Ø19,9 mm			Art. no.	12500112		
									EAN no.	5703435031025		
						Sensor end-cap brass for Flexpipe Ø6,7 mm	Package 60 x Ø12 mm, size 60 x Ø12 mm, inner Ø6,7 mm, inner Ø10 mm			Art. no.	12500120	
										EAN no.	5703466111543	
							Accessory kit Elements Transition Pipe	Mounting kit for 3 m wire sensor			Art. no.	18055354
											EAN no.	5703466124420

For DEVIreg™ 850

Picture	Name	Description/Technical data	Art. no.	EAN no.
	Sensor tube and cap for DEVIreg™ 850	Installation tube for Ground Sensor DEVIreg™ 850 Ø 93 x 98	19119977	5703466208359
	PSU CP-D 24/2.5 100-240VAC/24VDC DINrail	Primary switch mode Power Supply Unit for DEVIreg 850. Input voltage 100-240 VAC, 47-63 Hz Output voltage 24 VDC (24-28 VDC) Output current/power, max 2,5 A / 60 W Ambient temp., operation -10...+70 °C IP class IP20 Mounting on DIN-rail Dimensions (H/W/D) 54 x 90 x 55 mm	140F1089	5703466209721

Accessories and spare parts for other heating elements

Picture	Name	Description/Technical data	Art. no.	EAN no.
	Wall mounting for DEVItemp™ cabin A	Package 280 x 40 x 130 mm	19400514	5703435010464
	Wall mounting for DEVItemp™ cabin B	Package 360 x 150 x 40 mm	19400522	5703435010471
	Button	Button for DEVItemp™ 115T, DEVItemp™ 121T	19001874	5703435001332
	Heating element 400 V, 2000 W	Heating element for DEVItemp™ 106T	23804776	5703466168752
	Heating element 400 V, 3000 W	Heating element for DEVItemp™ 109T	23804792	5703466208779
	Heating element 400 V, 3500 W	Heating element for DEVItemp™ 121T	23804594	5703464001761
	3-pole thermostat 0-40 °C, 125 °C	Thermostat for DEVItemp™ 303T	19002237	5703466096475
	3-pole thermostat 0-40 °C, 165 °C	Thermostat for DEVItemp™ 106T, DEVItemp™ 109T	19001297	5703464010909
	1-pole thermostat 0-40 °C	Thermostat for DEVItemp™ 115T, DEVItemp™ 121T	19001056	5703435001257
	1-pole thermal fuse 160 °C	Thermostat for DEVItemp™ 115T, DEVItemp™ 121T	19002211	5703464008524