

Installation guide

Solenoid valve

Type EV228BW 15-50 + Coil type BB/BE DC

132R9001

132R9001

≥ 297 Microns

1

2

3

4

5

6

7

8

9

10

Info for UK customers only: Danfoss Ltd., 22 Wyncolme End, HP9 1NB, GB

11

12 Only DC

13

14

[U] / Unlatched / Closed

[L] / Latched / Open

15

16

Drinking water approval			
 CERTIFIERAD 1002	 RI SE	Valid in	Certificate no.
356 Inspected by DTI		DK, SE	SCO155-18 *)
*) http://publiccert.extweb.sp.se/sv/Product/List/ Wetted parts in accordance with DVGW, 4MS, KTW and W270			

DN	Max. Working Pressure (MWP)	Max. Test pressure (PT)
	[bar]	[bar]
15 - 50	10	25
EN 60730-2-8		

Besök www.danfoss.se för mer tekniska data. Besøg www.danfoss.dk for flere tekniske data.
 Rendez-vous sur le site www.products.danfoss.fr pour plus de données techniques.
 Visit www.products.danfoss.com for further technical data. Para más información, visite www.products.danfoss.es

Any information, including, but not limited to information on selection of product, its application or use, product design, weight, dimensions, capacity or any other technical data in product manuals, catalogues descriptions, advertisements, etc. and whether made available in writing, orally, electronically, online or via download, shall be considered informative, and is only binding if and to the extent, explicit reference is made in a quotation or order confirmation. Danfoss cannot accept any responsibility for possible errors in catalogues, brochures, videos and other material. Danfoss reserves the right to alter its products without notice. This also applies to products ordered but not delivered provided that such alterations can be made without changes to form, fit or function of the product.
 All trademarks in this material are property of Danfoss A/S or Danfoss group companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. All rights reserved.