



Product Service

# Attestation of Conformity

No. N8A 18 01 84117 054

**Holder of Certificate:** **Osram GmbH**  
 Marcel-Breuer-Str. 6  
 80807 München  
 GERMANY

**Product:** **Electronic controlgear for LED modules  
 (24V Constant Voltage LED Power Supply)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

**Test report no.:** 64140170524101



**Date,** 2018-01-17

(Michael Xu)



After preparation of the necessary technical documentation as well as the EU conformity declaration the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

**Attestation of Conformity**  
**No. N8A 18 01 84117 054**

**Model(s):** OT 100/220-240/24 DIM P, OT 100/220-240/24 P,  
OT 130/220-240/24 DIM P, OT 130/220-240/24 P,  
OT 250/220-240/24 DIM P, OT 250/220-240/24 P

**Brand:** OSRAM

**Parameters:**

Rated Input:	220-240VAC, 50/60Hz or 176-250VDC
Protection against Electric Shock:	Class I; SELV
Degree of Protection:	IP67
Method of Installation:	Independent
Type of Output:	Constant voltage type
ta:	-30~55°C
tc:	85°C (OT 250/220-240/24 DIM P, OT 250/220-240/24 P); 80°C (other models)
Rated Output Voltage:	24VDC
Max. Output Voltage:	30VDC

Model	Rated max. output current (mA)
OT 100/220-240/24 DIM P	4420
OT 100/220-240/24 P	4420
OT 130/220-240/24 DIM P	5830
OT 130/220-240/24 P	5830
OT 250/220-240/24 DIM P	10420
OT 250/220-240/24 P	10420

Model	Rated Max. output power (W)
OT 100/220-240/24 DIM P	106
OT 100/220-240/24 P	106
OT 130/220-240/24 DIM P	140
OT 130/220-240/24 P	140
OT 250/220-240/24 DIM P	250
OT 250/220-240/24 P	250

**Tested according to:** EN 61347-1:2015  
EN 61347-2-13:2014/A1:2017  
EN 62493:2015