



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Rated Cross Section: **6 mm²**

Primary Product Color: **Gray**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Gauge Type	A5
Number of Levels	1
Number of Poles	2
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2

Electrical Characteristics

Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	150 V
Voltage Rating (CSA)	150 V
Current Rating (CSA)	40 A
Short-Time Withstanding Current Rating @ 1s	720 A
Voltage Rating (IEC)	630 V
Current Rating (UL)	40 A
Current Rating (IEC)	40 A
Voltage Rating	630 VAC

Body Features



Product Weight	20 g[.705 oz]
----------------	---------------

Primary Product Color	Gray
-----------------------	------

Termination Features

Termination Method to Wire & Cable	Screw Terminal
------------------------------------	----------------

Mechanical Attachment

DIN Rail Mounting Type	G32, TH35-15, TH35-7.5
------------------------	------------------------

Tightening Torque	7.1 in-lbs
-------------------	------------

Connector Mounting Type	DIN Rail
-------------------------	----------

Housing Features

Housing Material	Polyamide 6.6
------------------	---------------

Dimensions

Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	.5 – 10 mm²
--	-------------

Wire Stripping Length	13 mm[.512 in]
-----------------------	----------------

Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 6 mm²
---	------------

Tool Size	5 mm[.197 in]
-----------	---------------

Product Depth	41 mm
---------------	-------

Product Width	8 mm[.314 in]
---------------	---------------

Product Length	41 mm
----------------	-------

Product Height	77 mm
----------------	-------

Rated Cross Section	6 mm²
---------------------	-------

Product Spacing	8 mm[.314 in]
-----------------	---------------

Wire Size	6 mm²
-----------	-------

Usage Conditions

Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
---------------------------	----------------------------

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
--------------------------------	-------------------------

Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1SNA114522R0500
SCFT2



TE Part # 1SNA116538R1700
PC8-2



TE Part # 1SNA116539R1000
PC8-3




TE Part # 1SNA116540R2500
PC8-4




 TE Part # 1SNA163313R2400 PC8-10	 TE Part # 1SNA173060R0000 DCO	 TE Part # 1SNA234000R0200 RC810	 TE Part # 1SNA400711R0600 PC8-R1
 TE Part # 1SNA400712R0700 PC8-R2	 TE Part # 1SNA400713R0000 PC8-R3	 TE Part # 1SNA400724R0300 PC8-R4	 TE Part # 1SNA400842R0000 PC8-R5
 TE Part # 1SNA400843R0000 PC8-R6	 TE Part # 1SNA400849R0000 PC8-R7	 TE Part # 1SNA400850R0000 PC8-R8	 TE Part # 1SNA113629R2700 FEMT2
 TE Part # 1SNA114205R2000 AD2.5	 TE Part # 1SNA168401R0300 EV8S	 TE Part # 1SNA174789R0500 BJS8-20	 TE Part # 1SNA399903R0200 BADL

Also in the Series | ENTRELEC SNA

 Modular Terminal Blocks(182)	 Terminal Block & Strip Conducting Accessories(26)	 Terminal Block & Strip Insulating Accessories(14)
---	--	--

Customers Also Bought






TE Part #1SNA105120R2600
M10/10



TE Part #1SNA115236R1700
M6/8.ST



TE Part #1SNA232000R0000
RC65



TE Part #1SNA234041R2600
RC810 1->10 (X10) VERTICAL



TE Part #1SNA234042R2700
RC810 11->20 (X10) VERTICAL




TE Part #1SNK900654R0000
SC-JB8-4




TE Part #1SNA116522R0700
BFU2.S12.G



TE Part #1SNA168203R1400
CPP312



TE Part #1SNA193629R2000
FEMT2-BE



TE Part #1SNA199336R2000
FEDAD1

Documents

- CAD Files

Customer View Model

ENG_CVM_CVM_1SNA115243R2600_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNA115243R2600_B.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1SNA115243R2600_B.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

- Datasheets & Catalog Pages

Catalogue - ENTRELEC terminal-blocks-sna-series

English

M6/8.ST7

English

1SNA115243R2600

Modular Terminal Blocks, Feed-Through, Screw Clamp Terminal Block, Gray, Product
Spacing .314 in [8 mm], 2 Position, Screw Terminal, ENTRELEC SNA



[ENTRELEC Terminal Block - Master Catalog](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)