## 1SNA115604R2100 - ACTIVE



### ENTRELEC | ENTRELEC SNA

TE Internal #: 1SNA115604R2100

Modular Terminal Blocks, Fuse, Screw Clamp Terminal Block, Gray, Product Spacing .314 in [8 mm], 2 Position, Screw Terminal, Signal,

**ENTRELEC SNA** 

View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: Fuse

Modular Terminal Block Product Type: Screw Clamp Terminal Block

Rated Cross Section: 4 mm<sup>2</sup> Primary Product Color: Gray

### **Features**

### **Product Type Features**

Modular Terminal Block Product Type	Screw Clamp Terminal Block
Configuration Features	
Gauge Type	A4
Number of Levels	2
Number of Poles	4
Number of Circuits	2
Block Function	Fuse
Number of Positions	2
Electrical Characteristics	
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	300 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Voltage Rating (CSA)	250 V
Current Rating (CSA)	10 A
Voltage Rating (IEC)	630 V
Current Rating (UL)	20 A
Current Rating (IEC)	6.3 A
Voltage Rating	630 VAC
Body Features	



Product Weight	26 g[.917 oz]
Primary Product Color	Gray
Termination Features	
Termination Method to Wire & Cable	Screw Terminal
Mechanical Attachment	
DIN Rail Mounting Type	G32, TH35-15, TH35-7.5
Tightening Torque	4.4 in-lbs
Terminal Block Disconnect Type	Lever
Connector Mounting Type	DIN Rail
Housing Features	
Housing Material	Polyamide 6.6
Dimensions	
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	.5 – 6 mm²
Wire Stripping Length	9.5 mm[.374 in]
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 4 mm²
Tool Size	4 mm[.157 in]
Product Depth	59 mm
Product Width	8 mm[.314 in]
Product Length	59 mm
Product Height	85.7 mm
Rated Cross Section	4 mm <sup>2</sup>
Product Spacing	8 mm[.314 in]
Wire Size	4 mm <sup>2</sup>
Usage Conditions	
Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
IP Rating	IP20



**UL Flammability Rating** 

UL 94V-0

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts






















TE Part # 1SNA008288R1500 FU520

TE Part # 1SNA008290R1300 FU520

TE Part # 1SNA008291R0000 FU520

TE Part # 1SNA008292R0100 FU520

TE Part # 1SNA114205R2000 AD2.5

TE Part # 1SNA116900R2700 **BADH** 

TE Part # 1SNA116913R0700 FEM8D2S





TE Part # 1SNA167860R0100 FC4

TE Part # 1SNA168672R1100 TGA8

## Also in the Series | ENTRELEC SNA







Terminal Block & Strip Conducting Accessories(26)



Terminal Block & Strip Insulating Accessories(14)

# Customers Also Bought





TE Part #1SNA105075R2000 MA2.5/5



TE Part #1SNA105077R2200 MA2.5/5



TE Part #1SNA115479R2300 M4/6.4A



D2.5/6.DA




TE Part #1SNA400184R2700 MA2.5/5



TE Part #1SNA116913R0700 FEM8D2S







FEM6D

### **Documents**

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1SNA115604R2100\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNA115604R2100\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNA115604R2100\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

Catalogue - ENTRELEC terminal-blocks-sna-series

English

M4/8.D2.SF

English

Modular Terminal Blocks, Fuse, Screw Clamp Terminal Block, Gray, Product Spacing . 314 in [8 mm], 2 Position, Screw Terminal, Signal, ENTRELEC SNA



**ENTRELEC Terminal Blocks Catalogue (RUS)**