1SNK508066R0000 - ACTIVE



ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK508066R0000

Modular Terminal Blocks, Feed-Through, Screw Clamp Terminal Block, Black, Product Spacing .315 in [8 mm], 2 Position, DIN Rail,

ENTRELEC SNK

View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks









Screw Clamp Terminal Block



Block Function: Feed-Through

Modular Terminal Block Product Type: Screw Clamp Terminal Block

Rated Cross Section: 10 mm² Primary Product Color: Black

Modular Terminal Block Product Type

Features

Product Type Features

| Configuration Features | |
|----------------------------|--------------|
| Gauge Type | A5-B5 |
| Number of Levels | 1 |
| Number of Circuits | 1 |
| Block Function | Feed-Through |
| Number of Positions | 2 |
| Electrical Characteristics | |

| Impulse Withstanding Voltage Rating (IEC) | 8000 V |
|--|--------|
| Current Rating (CSA) | 42 A |
| Power Loss | 1.8 W |
| Short-Time Withstanding Current Rating @ 1s | 1200 A |
| Voltage Rating (IEC) | 1000 V |
| Operating Voltage Rating (UL & CSA) (Max) - Main Circuit | 600 V |
| Voltage Rating (CSA) | 600 V |



| Dielectric Test Voltage | 2200 V |
|---|----------------------------|
| Current Rating (UL) | 42 A |
| Current Rating (IEC) | 57 A |
| Body Features | |
| Product Weight | 14.1 g[.555 oz] |
| Primary Product Color | Black |
| Mechanical Attachment | |
| DIN Rail Mounting Type | TH35-15, TH35-7.5 |
| Connector Mounting Type | DIN Rail |
| Housing Features | |
| Housing Material | Polyamide |
| Dimensions | |
| Main Circuit Capacity - Twin Ferrule per Screw Clamp | 20 – 12 AWG |
| Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp | 24 – 6 AWG |
| Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp | 24 – 10 AWG |
| Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp | $.5 - 10 \text{ mm}^2$ |
| Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp | .5 – 4 mm² |
| Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp | 24 – 6 AWG |
| Wire Stripping Length | 12 mm[.472 in] |
| Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp | .5 – 4 mm² |
| Tool Size | 4 mm[.157 in] |
| Product Depth | 47.3 mm |
| Product Length | 47.3 mm[1.86 in] |
| Product Height | 53 mm |
| Rated Cross Section | 10 mm² |
| Product Spacing | 8 mm[.315 in] |
| Usage Conditions | |
| Storage Temperature Range | -55 – 110 °C[-67 – 230 °F] |
| Installation Temperature Range | -5 - 40 °C[23 - 104 °F] |
| Operating Temperature Range | -55 – 110 °C[-67 – 230 °F] |
| | |

Industry Standards



| IP Rating | IP20 |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











































Also in the Series | ENTRELEC SNK







Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(30)

Customers Also Bought





















Documents

CAD Files

Customer View Model

ENG_CVM_CVM_1SNK508066R0000_A1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508066R0000_A1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508066R0000_A1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

English

ZS10-BK

English

Modular Terminal Blocks, Feed-Through, Screw Clamp Terminal Block, Black, Product Spacing .315 in [8 mm], 2 Position, DIN Rail, ENTRELEC SNK



SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Agency Approvals

ZK-ZS_ATEX_1SND225112U1006-C-TE

English