



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Disconnect**
Modular Terminal Block Product Type: **Screw Clamp Terminal Block**
Rated Cross Section: **10 mm²**
Primary Product Color: **Gray**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Gauge Type	A5-B5
Number of Levels	1
Number of Poles	2
Number of Circuits	1
Block Function	Disconnect
Number of Positions	2

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (CSA)	53 A
Power Loss	2.6 W
Short-Time Withstanding Current Rating @ 1s	1200 A
Voltage Rating (IEC)	630 V
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	300 V



Voltage Rating (CSA)	300 V
Dielectric Test Voltage	2000 V
Current Rating (UL)	53 A
Current Rating (IEC)	50 A

Body Features

Product Weight	31.9 g[1.256 oz]
Primary Product Color	Gray

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Terminal Block Disconnect Type	Sliding Link
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Main Circuit Capacity - Twin Ferrule per Screw Clamp	20 – 12 AWG
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	24 – 6 AWG
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	24 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	.5 – 10 mm²
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	.5 – 4 mm²
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 6 AWG
Wire Stripping Length	13 mm[.512 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	.5 – 4 mm²
Tool Size	3.5 mm[.138 in]
Product Depth	61.1 mm
Product Length	61.1 mm[2.41 in]
Product Height	80.7 mm
Rated Cross Section	10 mm²
Product Spacing	8 mm[.315 in]

Usage Conditions

Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
Installation Temperature Range	-5 – 40 °C[23 – 104 °F]



Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
-----------------------------	----------------------------

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>




EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Pb (3.5% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # 1SNK900001R0000 BAM4	 TE Part # 1SNK900002R0000 BAZ1	 TE Part # 1SNK900102R0000 BAZH1	 TE Part # 1SNK900107R0000 CS-R3
 TE Part # 1SNK900624R0000 KCO	 TE Part # 1SNK900653R0000 SC-JB8-3	 TE Part # 1SET111016R0000 WF060-12-GN	 TE Part # 1SET111035R0000 WF060-12-YL
 TE Part # 1SET112009R0000 WFD040-12-OR	 TE Part # 1SET112015R0000 WFD040-12-GR	 TE Part # 1SNA116538R1700 PC8-2	 TE Part # 1SNA116539R1000 PC8-3
 TE Part # 1SNA116540R2500 PC8-4	 TE Part # 1SNA163313R2400 PC8-10	 TE Part # 1SNA400711R0600 PC8-R1	 TE Part # 1SNA400712R0700 PC8-R2
 TE Part # 1SNA400713R0000 PC8-R3	 TE Part # 1SNA400724R0300 PC8-R4	 TE Part # 1SNA400842R0000 PC8-R5	 TE Part # 1SNA400843R0000 PC8-R6


Also in the Series | **ENTRELEC SNK**



Modular Terminal Blocks(318)



Terminal Block & Strip Conducting Accessories(67)




Terminal Block & Strip Insulating Accessories(30)

Customers Also Bought



TE Part #1SNK505910R0000
ES4




TE Part #1SNK506310R0000
ZS4-S-R1



TE Part #1SNK508410R0000
ZS4-SF1



TE Part #1SNA190005R2400
D300/55.FF



TE Part #1SNK506412R0000
ZS4-SF-R1



TE Part #1SNK508010R0000
ZS10



TE Part #1SNK508312R0000
ZS10-ST-1



TE Part #1SNK900205R0000
TP4



TE Part #1SNK900605R0000
LH



TE Part #1SNK900622R0000
PL16

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK508311R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508311R0000_A.3d_igs.zip

1SNK508311R0000

Modular Terminal Blocks, Disconnect, Screw Clamp Terminal Block, Gray, Product
Spacing .315 in [8 mm], 2 Position, DIN Rail, ENTRELEC SNK



English

Customer View Model

[ENG_CVM_CVM_1SNK508311R0000_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ENTRELEC Terminal Block - Master Catalog](#)

English

[ZS10-ST-T4](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)