# 1SNK708010R0000 ACTIVE



#### ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK708010R0000

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block,

Gray, Product Spacing .315 in [8 mm], 2 Position, DIN Rail,

ENTRELEC SNK

View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks









PI-Spring Terminal Block



Block Function: Feed-Through

Modular Terminal Block Product Type: PI-Spring Terminal Block

Rated Cross Section: 6 mm<sup>2</sup> Primary Product Color: Gray

### **Features**

### **Product Type Features**

Modular Terminal Block Product Type

Configuration Features	
Gauge Type	A5 & 3.9 mm Dia.
Number of Levels	1
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2

### **Electrical Characteristics**

Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (CSA)	50 A
Power Loss	1.3 W
Short-Time Withstanding Current Rating @ 1s	720 A
Voltage Rating (IEC)	1000 V
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Voltage Rating (CSA)	600 V



Dielectric Test Voltage	2200 V
Current Rating (UL)	50 A
Current Rating (IEC)	41 A
Body Features	
Product Weight	11.8 g[.465 oz]
Primary Product Color	Gray
Mechanical Attachment	
DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail
Housing Features	
Housing Material	Polyamide
Dimensions	
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	.5 – 10 mm²
Main Circuit Capacity - Twin Ferrule per Spring Clamp	$.5 - 1.5 \text{ mm}^2$
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 6 mm²
Wire Stripping Length	12.5 mm[.492 in]
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	.5 – 6 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	24 – 10 AWG
Tool Size	3.5 mm[.138 in]
Product Depth	41.9 mm
Product Length	41.9 mm
Product Height	57.5 mm
Rated Cross Section	6 mm <sup>2</sup>
Product Spacing	8 mm[.315 in]
Usage Conditions	
Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Industry Standards	
IP Rating	IP20
UL Flammability Rating	UL 94V-0



### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts













TE Part # 1SNK900001R0000 BAM4



TE Part # 1SNK900102R0000
BAZH1



























### Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(318)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(30)

### Customers Also Bought









=TE TE Part #1SNK910305R0000 JB10-5

TE Part #1SNK705150R0000 ZK2.5-PE



ZK10-PE





TE Part #1SNK710020R0000 ZK10-BL

TE Part #1SNK706020R0000 ZK4-BL









#### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK708010R0000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK708010R0000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1SNK708010R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

**ENTRELEC Terminal Block - Master Catalog** 

English

ZK6

English

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Gray, Product Spacing .315 in [8 mm], 2 Position, DIN Rail, ENTRELEC SNK



**SNK SERIES TERMINAL BLOCKS** 

English

**ENTRELEC Terminal Blocks Catalogue (RUS)** 

**Essential Entrelec Terminal Blocks** 

French

**Essential Entrelec Terminal Blocks** 

English

**Agency Approvals** 

Agency Approval Document

English