
1SNK805013R0000 ACTIVE



ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK805013R0000

Modular Terminal Blocks, Feed-Through & Pluggable, Screw Clamp Terminal Block, Gray, Product Spacing .205 in [5.2 mm], 4 Position,

ENTRELEC SNK

View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks









Screw Clamp Terminal Block



Block Function: Feed-Through & Pluggable

Modular Terminal Block Product Type

Modular Terminal Block Product Type: Screw Clamp Terminal Block

Rated Cross Section: 4 mm² Primary Product Color: Gray

Features

Product Type Features

Configuration Features	
Gauge Type	A3-B3
Number of Levels	1
Number of Circuits	1
Block Function	Feed-Through & Pluggable
Number of Positions	4

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (CSA)	28 A
Power Loss	1 W
Short-Time Withstanding Current Rating @ 1s	480 A
Voltage Rating (IEC)	800 V
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	300 V
Voltage Rating (CSA)	300 V



Dielectric Test Voltage	2200 V
Current Rating (UL)	28 A
Current Rating (IEC)	29 A
Body Features	
Product Weight	10.75 g[.429 oz]
Primary Product Color	Gray
Mechanical Attachment	
DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail
Housing Features	
Housing Material	Polyamide
Dimensions	
Main Circuit Capacity - Twin Ferrule per Screw Clamp	24 – 16 AWG
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	.22 – 4 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	24 – 12 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	$.22 - 4 \text{ mm}^2$
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 10 AWG
Wire Stripping Length	10.5 mm[.413 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	.2 – 1.5 mm²
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	.22 – 1.5 mm²
Tool Size	3.5 mm[.138 in]
Product Depth	47.4 mm
Product Length	80.3 mm
Product Height	80.3 mm
Rated Cross Section	4 mm ²
Product Spacing	5.2 mm[.205 in]
Usage Conditions	
Storage Temperature Range	-55 – 110 °C[-67 – 230 °F]
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards



IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













TE Part # 1SNK900102R0000 BAZH1



TE Part # 1SNK900203R0000 TP2



























Also in the Series | ENTRELEC SNK







Customers Also Bought













TE Part #1SNK900630R0000 MCLH



TE Part #1SNA166646R0500 CPT-1 TE Part #1SNA166747R0200 TC-E-VA

TE Part #1SNA166878R0600 DEO-E-VA

TE Part #1SNA166926R1600 CPDE-2

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK805013R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK805013R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK805013R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

English

ZDS4-22

English

Modular Terminal Blocks, Feed-Through & Pluggable, Screw Clamp Terminal Block, Gray, Product Spacing .205 in [5.2 mm], 4 Position, ENTRELEC SNK



SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Agency Approvals

UL

English