




MIKRO Spot Rail 2800lm

Tracklight, White, 3 Circuits, 39W, Triac Dim, 3CCT, 50000H

Model No.: LUMIK03
SGSO Sku: 0017440094
GTIN/EAN: 7630268409333

Suitable for surface mounting:	Yes
Suitable for suspended mounting:	Yes
Suitable for ceiling mounting:	Yes
Suitable for light-track mounting:	Yes
Adjustability:	Rotating and swivelling
Lamp type:	LED not exchangeable
With light source:	Yes
Suitable for number of lamps:	1
Lamp holder:	Other
Material housing:	Aluminium
Colour housing:	White
Material cover:	Glass transparent
Voltage type:	AC
Nominal voltage:	220 ... 240 V
LED nominal current at constant current:	950 mA
Type of control gear:	Electronic transformer
With control gear:	Yes
Beam angle:	Medium beam 21-40°
Light outlet:	Direct
Rated life time L70/B50 at 25 °C:	50000 h
Degree of protection (IP):	IP20
Impact strength:	IK02
Protection class:	I
Rated ambient temperature according to IEC62722-2-1:	-20 ... 40 °C
Suitable for lamp power:	39 W
Max. system power:	39 W
Colour of light:	White
Colour temperature:	3000 ... 5000 K
Colour rendering index CRI:	90-100
Luminous flux:	2800 lm
Rated luminous flux according to IEC 62722-2-1:	2800 lm
Power factor:	0.9
Height/depth:	303 mm
Outer diameter:	90 mm
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Luminaire efficacy:	71 lm/W
Colour consistency (McAdam ellipse):	SDCM4



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

