




MIKRO Spot Rail 1050lm

Tracklight, Black, 3 Circuits, 14W, Triac Dim, 3CCT, 50000H,

Model No.: LUMIK04
SGSO Sku: 0017440095
GTIN/EAN: 7630268409340

| | |
|--|-------------------------|
| Suitable for surface mounting: | Yes |
| Suitable for suspended mounting: | Yes |
| Suitable for ceiling mounting: | Yes |
| Suitable for light-track mounting: | Yes |
| Adjustability: | Rotating and swivelling |
| Lamp type: | LED not exchangeable |
| With light source: | Yes |
| Suitable for number of lamps: | 1 |
| Lamp holder: | Other |
| Material housing: | Aluminium |
| Colour housing: | Black |
| Material cover: | Glass transparent |
| Voltage type: | AC |
| Nominal voltage: | 220 ... 240 V |
| LED nominal current at constant current: | 340 mA |
| Type of control gear: | Electronic transformer |
| With control gear: | Yes |
| Beam angle: | Medium beam 21-40° |
| Light outlet: | Direct |
| Rated life time L70/B50 at 25 °C: | 50000 h |
| Degree of protection (IP): | IP20 |
| Impact strength: | IK02 |
| Protection class: | I |
| Rated ambient temperature according to IEC62722-2-1: | -20 ... 40 °C |
| Suitable for lamp power: | 14 W |
| Max. system power: | 14 W |
| Colour of light: | White |
| Colour temperature: | 3000 ... 5000 K |
| Colour rendering index CRI: | 90-100 |
| Luminous flux: | 1050 lm |
| Rated luminous flux according to IEC 62722-2-1: | 1050 lm |
| Power factor: | 0.9 |
| Height/depth: | 230 mm |
| Outer diameter: | 60 mm |
| Filament test according to IEC 60695-2-11: | 650 °C - 30 s |
| Luminaire efficacy: | 75 lm/W |
| Colour consistency (McAdam ellipse): | SDCM4 |



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

