



DALI Driver 32

Driver 32 , Dali,CII, White, 100 000H, W/O Box, W/
Quick connector, Linkable

ID: 0027100052

GTIN: 7630268417550



5 YEARS *
WARRANTY

Technical Data

Model:	Static
Dimming DALI:	Yes
Dimming with push-button:	Yes
Housing:	Plastic housing
Suitable for constant current:	Yes
Output voltage:	30 ... 40 V
Output current:	850 mA
Output power:	27.2 ... 34 W
Power consumption:	0.5 W
Degree of protection (IP):	IP20
Protection class:	II
Length:	163 mm
Width:	60.5 mm
Height:	27 mm

Additional Information

Power factor	0.9
Lifetime L70	100000H
Lifetime L80	100000H
Dimming Range	1% ~ 100%
Dali standby power	0.5W
Control gear	YES
Linkable Qty B16	18
Linkable Qty C16	29
Linkable Qty B10	11
Linkable Qty C10	21
Temperature range	-20...40°C
Cable connection	Push terminal
Cable length(input/output)	NA/14cm
Cable cross-section(input/output)	NA/2*0.5mm ²
Inrush current	18A
Surge capability(L/N-G)	N/A
Surge capability(L-N)	1KV
Certification/Norms	CE/REACH/RoHS/DALI2
SELV	YES
Overheating protection	YES
Overload protection	YES
No-load protection	YES
Short-circuit protection	YES
Covering with thermal insulating material or not	NO
Product weight	153g
Product weight with packaging	187g
Compatible panel	PALMA,PALMA+,MALTA.,MALTA+

