



# Batten IP20 1220mm Sensor

## Batten 1220mm Tricolour Dual Wattage 20W/40W 3000K/4000K/6500K IP20 Sensor NDIM

**Model No.:** 994772403  
**SGSO Sku:** 0028920096  
**GTIN/EAN:** 7630268407025

Suitable for ceiling mounting:	Yes
Suitable for surface mounting:	Yes
Lamp type:	LED not exchangeable
With light source:	Yes
Suitable for number of lamps:	1
Lamp holder:	None
Material housing:	<b>SPCC</b>
Colour housing:	White
Material cover:	Plastic, opal
Voltage type:	AC
Nominal voltage:	220 ... 240 V
Nominal current:	100/200 <b>mA</b>
Type of control gear:	LED operating device current--
With control gear:	yes
No dim function:	Yes
Light distributor:	Diffuser lens/optic/panel
Light sharing:	Symmetric
Beam angle:	Open beam/diffuse
Colour consistency (McAdam ellipse):	SDCM6
Energy efficiency class of the built-in lamp:	Other
Rated life time L70/B50 at 25 °C:	50000 h
Rated life time L80/B10 at 25 °C:	30000 h
Rated life time L90/B10 at 25 °C:	15000 h
Degree of protection (IP):	IP20
Impact strength:	IK08
Protection class:	I
Rated ambient temperature according to IEC62722-2-1:	-20 ... 40 °C
Suitable for emergency lighting:	<b>No</b>
Covering of the luminaire with thermally insulating material possible:	<b>No</b>
Filament test according to IEC 60695-2-11:	650 °C - 30 s
Suitable for lamp power:	20/40 <b>W</b>
Max. system power:	40 W
Luminaire efficacy:	125 lm/W
Rated luminous flux according to IEC 62722-2-1:	2500/5000
Colour of light:	Other
Colour temperature:	3000/4000/6500 <b>K</b>
Colour rendering index CRI:	80-89
Power factor:	0.9
Width:	70 mm
Height/depth:	76.5 mm
Length:	1220 mm
Unified Glare Ratio (UGR):	25

