



# Jack

## Bulkhead,8.5/12.5W,1020/1500lm,120lm/W,3 CCT 2700 K+3000K+4000K,IP54,On/Off,White,MW Corridor Sensor

**Model No.:**

**SGSO Sku:**

**0028920232**

**GTIN/EAN:**

**7630268419066**

|                                                                                   |                                         |
|-----------------------------------------------------------------------------------|-----------------------------------------|
| Suitable for wall mounting:                                                       | Yes                                     |
| Suitable for ceiling mounting:                                                    | Yes                                     |
| Suitable for surface mounting:                                                    | Yes                                     |
| Lamp type:                                                                        | LED not exchangeable                    |
| Housing material:                                                                 | Plastic                                 |
| Surface protection housing:                                                       | Untreated                               |
| Housing colour:                                                                   | White                                   |
| Material cover:                                                                   | Plastic, opal                           |
| Type of grid:                                                                     | None                                    |
| Voltage type:                                                                     | AC                                      |
| Nominal voltage:                                                                  | 220 ... 240 V                           |
| Nominal current:                                                                  | 40 ... 58 mA                            |
| Type of control gear:                                                             | LED operating device current-controlled |
| No dim function:                                                                  | Yes                                     |
| Light distributor:                                                                | Diffuser lens/optic/panel               |
| Light sharing:                                                                    | Symmetric                               |
| Beam angle:                                                                       | Extreme wide beam >80°                  |
| Colour consistency (McAdam ellipse):                                              | SDCM4                                   |
| Light outlet:                                                                     | Indirect                                |
| Energy efficiency class of the light source according to EU regulation 2019/2015: | C                                       |
| Rated life time L70/B50 at 25 °C:                                                 | 60000 h                                 |
| Max. number of luminaires per miniature circuit breaker B 16 (MCB):               | 27                                      |
| Max. number of luminaires per miniature circuit breaker C 16 (MCB):               | 46                                      |
| Degree of protection (IP):                                                        | IP54                                    |
| Degree of protection (NEMA):                                                      | Other                                   |
| Impact strength:                                                                  | IK08                                    |
| Protection class:                                                                 | II                                      |
| Rated ambient temperature according to IEC 62722-2-1:                             | -20 ... 45 °C                           |
| With movement sensor:                                                             | Yes                                     |
| Filament test according to IEC 60695-2-11:                                        | 750 °C - 30 s                           |
| Suitable for lamp power:                                                          | 8.3 ... 12.5 W                          |
| Max. system power:                                                                | 12.5 W                                  |
| Luminaire efficacy:                                                               | 120 lm/W                                |
| Colour of light:                                                                  | White                                   |
| Colour temperature:                                                               | 2700 ... 4000 K                         |
| Flickering value Pst LM:                                                          | 0                                       |
| Colour rendering index CRI:                                                       | 80-89                                   |
| Power factor:                                                                     | 0.9                                     |
| Stroboscope effect value SVM:                                                     | 0.4                                     |
| Width:                                                                            | 220 mm                                  |
| Height/depth:                                                                     | 52 mm                                   |
| Length:                                                                           | 220 mm                                  |
| Outer diameter:                                                                   | 220 mm                                  |
| Type of wiring:                                                                   | Ending                                  |
| Number of poles:                                                                  | 2                                       |
| Conductor cross section:                                                          | 0.5 mm <sup>2</sup>                     |
| Connection type:                                                                  | Push-in clamp                           |
| Total harmonic distortion:                                                        | 15                                      |
| Photobiological safety according to EN 62471:                                     | RG0                                     |
| Unified Glare Ratio (UGR):                                                        | 26                                      |
| Colour of light adjustable:                                                       | Positions                               |
| Luminous flux adjustable:                                                         | Positions                               |

