

ETANCHE LED

Réf / Ref	Désignation / Designation	Puis. / Power	Temp K° / Color
BL11366504	TF115-ETANCHE TECH-120-36W-4000K-TRAVERSANT-IP66-IK10	36W	4000K
BL11426505	TF116-ETANCHE TECH-150-42W-4000K-TRAVERSANT-IP66	42W	4000K
BL11636502	TF141-ETANCHE TECH-150-55W-4000K-TRAVERSANT-IP66-IK10	55W	4000K
BL11586503	TF104-ETANCHE TECH 150-42W-IP66-IK10-OPAL-3000K-850°	42W	3000K
BL11366502	TF103-ETANCHE TECH 120-36W-IP66-IK10-OPAL-3000K-850°	36W	3000K
BL11366507	TF142-ETANCHE TECH DETECT-120-36W-4000K-IP66-IK10-TRAVERSANT	36W	4000K
BL11636505	ETANCHE TECH 150-54W-7800LM-5000K-IP65	54W	5000K
BL11366505	ETANCHE TECH-120-36W-4000K-DALI	36W	4000K
BL11636503	ETANCHE TECH 150-62W-5000K-IP66	34W - 43W - 52W - 62W	5000K
BL11186508	ETANCHE TECH-650-18W-2CCT-4K5K-IP65-TRAV	18W	4000K-5000K
BL11366512	ETANCHE TECH DALI PUSH DIM 120-36W-4000K-IP66-IK10	36W	4000K
BL11426511	ETANCHE TECH DALI PUSH DIM 150-42W-4000K-IP66-IK10	42W	4000K
BL11366503	ETANCHE TECH-120-36W-4000K-TRAV-IP66-EMERGENCY	36W	4000K
BL11626601	ETANCHE TECH-150-62W-6500K	62W	6500K
BL1162660X	ETANCHE TECH-150-70W-4000K	70W	4000K
BL11362105	ETANCHE TECH-120-37W-4000K-IP66-IK10-TRAVERSANT	37W	4000K
BL11362106	ETANCHE TECH-SENSOR-120-22W-4000K-IP66-IK10-TRAVERSANT-PREAVIS EXTINCTION	22W - 27W - 32W - 38W	4000K
BL11362107	ETANCHE TECH-120-35W-4000K-IP66-IK10-TRAVERSANT-DALI PUSH DIM	35W	4000K
BL11422108	ETANCHE TECH-150-31W-4000K-IP66-IK10-TRAVERSANT	24W - 31W - 36W - 42W	4000K
BL11422109	ETANCHE TECH-150-58W-4000K-TRAVERSANT-IP66-IK10	35W - 44W - 52W - 58W	4000K
BL11432110	ETANCHE TECH SENSOR-150-31W-4000K-IP66-IK10-TRAVERSANT-PREAVIS EXTINCTION	24W - 31W - 36W - 42W	4000K

Par le présent document, les produits répertoriés ci-dessus sont certifiés conformes aux directives et normes suivantes :

Directives Européennes / European Directives

RoHS 2011/65/EU

CEM 2014/30/EU

DBT 2014/35/EU

RoHS 2015/863/EU

RoHS 2017/2102/EU

ErP 2009/125/CE

EN 61547 :2009

EN 60598-2-1 :2021

EN 55015 :2019+A11 :2020

EN 61000-3-2 :2019+A1 :2021

EN 60598-2-24 :2013

EN 60598-1 :2021+AMD11 :2022

EN 62493:2015+A1:2022

EN 61000-3-3: 2013+A1: 2019+A2: 2021

Test de résistance au fil incandescent 850°C

Groupe du risque photo biologique : Groupe 0

Date d'émission du document : 26 Mai 2025

Signature



Laurent RENARD
Président