



DESCRIPTION

With the HELAFIX Kit HC, he is possible to identify his cable, wire or pipe easily and quickly. In fact, the kit contains T18I cables-ties, Helafix HC carrier, Helafix HFX labels and marker.

The versatile Helafix HC carriers are suitable for temporary or permanent marking. They are also easy to attach for temporary marking. Material and profile reliably protect the inserted label against damp, dirt, damage and UV radiation.

The Helafix HFX labels are resistant to a variety of solvents. Good UV light resistance. Use marking T82 or print the labels with laserprinter. For indoor use in bundle applications in machines, panel buiding or wherever flexible self marked marking ix needed.

The T18I cable tie are characterised by internal serrations allowing for a positive hold onto cable, hose and pipe bundles. The design of the head guarantees a high tensile strength whilst allowing a very low insertion force, this, combined with the bent tail design of many of ties, ensures a simple and quick installation.

APPLICATION

The HELAFIX Kit HC is used mainly in electrical market for the marking of cable looms, cables, pipes, transports systems, valves, sensors, for inventory marking on machines or other parts.

PROPERTIES

T18I CABLE TIE

| Properties | Typical Results |
|----------------------------------|----------------------|
| Material | Polyamide 66 (PA 66) |
| Continuous Operating Temperature | -40°C to +85°C |
| Intermittent Temperature | +105°C for 500H |
| Flammability | UL94 V2 |
| Tensile strength | 80 N |
| Colours | Natural (NA) |



HELAFIX HC CARRIER

| Properties | Typical Results |
|----------------------------------|-----------------------------------|
| Material | Polyethylene, UV résistant (PEUV) |
| Continuous Operating Temperature | -60°C to +65°C |
| Flammability | UL94 HB |
| Colours | Transparent (CL) |






HELAFIX HX LABELS

| Properties | Typical Results |
|----------------------------------|-------------------------|
| Material | Polyester |
| Continuous Operating Temperature | -70°C to +160°C |
| Paper format | A4 |
| Colours | Yellow (YE), White (WH) |






CONTENTS

HELAFIX KIT HC13

| DRAWING | DESCRIPTION | SIZE |
|--|-----------------------------|--------------|
|  | 100 Helafix carrier HC12-35 | 35 x 13 mm |
|  | 115 Helafix Labels HFX 17-P | 35 x 12 mm |
|  | 100 T18I cable tie | 140 x 2.5 mm |
| | 1 Black Marker | |

HELAFIX KIT HC25

| DRAWING | DESCRIPTION | SIZE |
|---|-----------------------------|--------------|
|  | 100 Helafix carrier HC25-52 | 52 x 25 mm |
|  | 36 Helafix Labels HFX 55-P | 210 x 24 mm |
|  | 100 T18I cable tie | 200 x 2.5 mm |
| | 1 Black Marker | |