

Inline Ratchet P-Clamp

Round Fir Tree Mount - 6.5 mm

The Inline Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.



Features and Benefits

- One-piece ratchet closure allows for easy installation during pre- or final assembly.
- Easy release feature simplifies quick adjustments and maintenance.
- Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.
- High-performing round fir trees mean no additional fastener is needed for mounting.



MATERIAL	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Operating Temperature**	-40°F to +221°F (-40°C to +105°C)
Flammability	UL 94 HB
Color	Black (BK)

RoHS ✓



PART NO.	TYPE	Min. Bundle Diameter in. (mm)	Max. Bundle Diameter in. (mm)	Min. Tensile Strength lbs. (N)	Mounting Hole Dia. in. (mm)	Panel Thickness in. (mm)	Fixation Method	Width (W) in. (mm)	Pkg. Qty.
156-02706	IRCAFT6.5LG	0.2 (6.1)	0.5 (13.7)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	25
156-02616		0.2 (6.1)	0.5 (13.7)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	250
156-02707	IRCBFT6.5LG	0.5 (12.7)	0.8 (19.6)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	25
156-02626		0.5 (12.7)	0.8 (19.6)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	250
156-02708	IRCCFT6.5LG	0.8 (19.3)	1.4 (36.0)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	25
156-02636		0.8 (19.3)	1.4 (36.0)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	250
156-02709	IRCDFT6.5LG	1.4 (36.0)	2.0 (50.8)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	25
156-02646		1.4 (36.0)	2.0 (50.8)	100.0 (445.0)	0.26 (6.5)	0.02 - 0.35 (0.6 - 9.0)	Fir tree for round holes	1.4 (34.9)	200

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.
 **Ratchet P-Clamps have been tested to -40°F to +257°F (-40°C to +125°C)

Bundling and Securing

Clamps

Inline Ratchet P-Clamp

Round Fir Tree Mount - 9 mm

The Inline Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.



Features and Benefits

- One-piece ratchet closure allows for easy installation during pre- or final assembly.
- Easy release feature simplifies quick adjustments and maintenance.
- Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.
- High-performing round fir trees mean no additional fastener is needed for mounting.



MATERIAL	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Operating Temperature**	-40°F to +221°F (-40°C to +105°C)
Flammability	UL 94 HB
Color	Black (BK)

RoHS ✓



PART NO.	TYPE	Min. Bundle Diameter in. (mm)	Max. Bundle Diameter in. (mm)	Min. Tensile Strength lbs. (N)	Mounting Hole Dia. in. (mm)	Panel Thickness in. (mm)	Fixation Method	Width (W) in. (mm)	Pkg. Qty.
156-02714	IRCAFT9LG	0.2 (6.1)	0.5 (13.7)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	25
156-02620		0.2 (6.1)	0.5 (13.7)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	250
156-02715	IRCBFT9LG	0.5 (12.7)	0.8 (19.6)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	25
156-02630		0.5 (12.7)	0.8 (19.6)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	250
156-02716	IRCCFT9LG	0.8 (19.3)	1.4 (36.0)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	25
156-02640		0.8 (19.3)	1.4 (36.0)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	250
156-02717	IRCDFT9LG	1.4 (36.0)	2.0 (50.8)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	25
156-02650		1.4 (36.0)	2.0 (50.8)	100.0 (445.0)	0.35 (9.0)	0.02 - 0.50 (0.6 - 12.7)	Fir tree for round holes	1.4 (34.9)	200

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.
 **Ratchet P-Clamps have been tested to -40°F to +257°F (-40°C to +125°C)