

## UK Declaration of Conformity

Nr : PKR5912100-01

**Products identification :**

Type of products : Electronic pressure sensors

Trademark : **Telemecanique Sensors**

Models : **XMLT...**  
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)** and **Yageo TMSS UK Limited (UK Representative)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following Regulation(s) :

Electromagnetic Compatibility Regulations : **SI 2016 No. 1091**

Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 : **SI 2012 No. 3032**

Product's conformity has been assessed by applying the following designated standard(s) :

**BS EN 61326-1:2013**

**BS EN 61326-2-3:2013**

**BS EN IEC 63000:2018**

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.



**Tony KUMETA**

General Manager, UK&I

Issued at : Harrogate – UNITED KINGDOM

Emission date : February 27<sup>th</sup>, 2024

**Manufacturer :**  
**TMSS France**

Tour Egho – 2 avenue Gambetta  
92400 Courbevoie – FRANCE

**UK Representative :**  
**Yageo TMSS UK Limited**

2 North Park Road  
Harrogate, HG1 5PA – UNITED KINGDOM

**Technical Documentation authority :**  
**TMSS France**

Boulevard Salvador Allende – ZI n°3  
16340 L'Isle d'Espagnac – FRANCE

## Appendix

**Nr : PKR5912100-01**

List of product models covered by the present UK Declaration of Conformity

<b>XMLT</b>	<b>040</b>	<b>B</b>	<b>D</b>	<b>2</b>	<b>9</b>	<b>0</b>
<b>I</b>	<b>II</b>	<b>III</b>	<b>IV</b>	<b>V</b>	<b>VI</b>	<b>VII</b>

<b>I</b>	<b>Product type</b>	
	<b>XMLT</b>	: Electronic pressure sensor, for railway applications
<b>II</b>	<b>Pressure range</b>	
	<b>...</b>	: ... = 3 digits giving the pressure range (in bar)
<b>III</b>	<b>Pressure unit and type of cell</b>	
	<b>B</b>	: Gauge bar, metallic cell
<b>IV</b>	<b>Electrical connection type</b>	
	<b>D</b>	: M12 / 4 pins connector (output on pin 3)
	<b>M</b>	: M12 / 4 pins connector (output on pin 4)
<b>V</b>	<b>Electrical output type</b>	
	<b>2</b>	: Analogue, 4...20 mA
	<b>7</b>	: Analogue, 0...10 V
<b>VI</b>	<b>Fluid connection type</b>	
	<b>9</b>	: 7/16" - 20 UNF 2B (female) with Schrader
<b>VII</b>	<b>Fluid sealing gasket type</b>	
	<b>0</b>	: Without sealing gasket

**NOTE** : These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.