

## UK Declaration of Conformity

Nr : BQT8604100-01

**Products identification :**

Type of products : Emergency stop trip wire switches

Trademark : **Telemecanique Sensors**

Models : **XY2CH1...**  
(complete list of models covered in page 2)

We, **TMSS France (Manufacturer)** and **Yageo TMSS UK Limited (UK Representative)**, declare under our sole responsibility that the products to which this declaration refers comply with Essential Requirements of the following Regulation(s) :

Supply of Machinery (Safety) Regulations : **SI 2008 No. 1597**

Electrical Equipment (Safety) Regulations : **SI 2016 No. 1101**

Electromagnetic Compatibility Regulations : **SI 2016 No. 1091**

Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 : **SI 2012 No. 3032**

Product's conformity has been assessed by applying the following designated standard(s) :

**BS EN ISO 13849-1:2015**

**BS EN ISO 13850:2015**

**BS EN 60204-1:2018**

**BS EN 60947-5-1:2017 + AC:2020**

**BS EN 60947-5-5:1997 + A1:2005 + A11:2013 + A2:2017**

**BS EN IEC 63000:2018**

When subject to installation, maintenance and use conforming to their intended purpose, to regulations and standards applicable in the country where they are installed, to the supplier's instructions and to accepted state of the art.



**Tony KUMETA**  
General Manager, UK&I

Issued at : Harrogate – UNITED KINGDOM

Emission date : February 27<sup>th</sup>, 2024

**Manufacturer :**  
**TMSS France**  
Tour Eqho – 2 avenue Gambetta  
92400 Courbevoie – FRANCE

**UK Representative :**  
**Yageo TMSS UK Limited**  
2 North Park Road  
Harrogate, HG1 5PA – UNITED KINGDOM

**Technical Documentation authority :**  
**TMSS France**  
Boulevard Salvador Allende – ZI n°3  
16340 L'Isle d'Espagnac – FRANCE

## Appendix

**Nr : BQT8604100-01**

List of product models covered by the present UK Declaration of Conformity

XY2CH	1	3	2	5	0	H29	TK
I	II	III	IV	V	VI	VII	VIII

I	<b>Product type</b>	
	XY2CH	: Rope pull switch with single anchor point
II	<b>Stop function</b>	
	1	: Emergency stop
III	<b>Position of the anchor point</b>	
	3	: Right
	4	: Left
IV	<b>Type of reset</b>	
	1	: Flush pushbutton
	2	: Booted pushbutton
	3	: Ø30 mushroom head pushbutton
	4	: Ø30 mushroom head pushbutton, operated by key n° 421
5	: Ø30 mushroom head pushbutton, operated by key n° 455	
V	<b>Contacts type for stop function</b>	
	5	: 1 NC + 1 NO, slow break (break before make)
	7	: 2 NC, slow break
9	: 2 NC + 1 NO, slow break (break before make)	
VI	<b>Pilot light type and supply voltage</b>	
	0	: Without pilot light
	3	: With 24 V AC or DC pilot light
7	: With 230 V AC pilot light	
VII	<b>Optional : Additional digit for cable entries type</b>	
	Blank	: Threaded holes for PG 13,5 cable gland
	H7	: Threaded holes for 1/2" NPT cable gland
H29	: Threaded holes for ISO M20 x 1,5 cable gland	
VIII	<b>Optional : Additional digit for protective treatment type</b>	
	Blank	: Normal protection
	TK	: Increased protection against corrosion

**NOTE :** These references may be followed by 1 to 3 alphanumeric digits, to denote assembly, marking or packaging variations, without impact on products characteristics and/or compliance.